

Internet Video Conferencing Phone



PLANET's latest Video Conferencing product, ICF-1600, brings you a vivid video conferencing experience through the Internet. Neither the PC nor the complex web camera is required for Internet video communications. Furthermore, the ICF-1600 has a built-in 7" LCD monitor in a telephone form factor ideal for desktop use.

The ICF-1600 is compliant with SIP standard, which brings you a seamless conferencing experience with other SIP compliant video conferencing systems, voice gateway, IP phones, ATA and IP PBX System. With SIP Proxy Server and MCU support, the ICF-1600 from PLANET makes quick and cost-effective communications possible for you and your business partners. The ICF-1600 has multiple video inputs which can be used to connect to external cameras for group meetings and/or a document camera for showing detailed documents or photographs. With up to 30 fps frame rate, outstanding picture and sound quality, the PLANET Internet Video Conferencing Phone offers you a superior communications experience via the Internet.

KEY FEATURES

- SIP version 2 (RFC 3261) compliant
- 7" Color TFT-LCD display with video / audio output function
- Built-in Web Browser for Internet navigation
- Personalize phone ring tone and screensaver
- Max. 30 Frames per Second
- Supports frame rate up to 30 fps
- User-friendly GUI / Web-based Management
- Support H.263 Video Codec and G.711, G.723.1, G.729A/B Audio Codec
- Compatible with SIP 2.0 Proxy server and peer to peer mode
- Built-in high quality CMOS camera
- Full-duplex Voice Conversation
- Superior voice quality with Voice Activity Detection (VAD), Automatic Gain Control(AGC), Acoustic Echo Cancellation(AEC) and Electrical Echo Cancellation(EEC) support

APPLICATIONS





SPECIFICATION

Product Internet Video Conferencing Phone

Model ICF-1600

Hardware

2 x 10/100Mbps RJ-45 port Port

CMOS module, 300K pixels QCIF, 30fps, Camera door Camera

USB 1 USB 1.1 (For connecting with USB mouse)

1 telephone handset Audio/Video Input 1 built-in microphone

1 built-in 7" TFT LCD, adjustable angle

Audio/Video Output 1 pair RCA Audio/Video output

1 built-in speaker

LFD indicator 1 PWR/INK LED

Protocols and Standard

SIP 2.0 RFC 3261 Standard Video Standard H.263, MPEG4

Audio Standard G.711a/u, G.723.1, G.729A/B TCP/IP, UDP, RTP/RTCP Internet protocol

Echo cancellation G.167

IEEE 802.3 Ethernet LAN standard IEEE 802.3u Fast Ethernet

Phone Features

1 Speaker phone Key 1 Headset Key

1 Volume Up & Down keys 1 Picture in picture enable key

Keys 1 Camera mute key

1 LCD/TV display toggle key 1 LCD Brightness Up & Down Keys

5 Speed dial Buttons 6 Soft keys

Silence Suppression Comfort noise generation(CNG)

voice activity detection (VAD)

In-band DTMF & Out-of-band DTMF (RFC 2833) Audio Features Call progress tone generation

Acoustic Echo Cancellation Dynamic Jitter buffer

Three-way audio conferencing

2-way Video Call PIP(Picture in Picture) LCD Brightness Adjustment

LCD Contrast Adjustment Video Features LCD/TV Display Switch

Video Privacy (Audio Only)

Video Mute

Remote Video Display On/Off

Address Book Phone setting

Message & **Configuration Service**

Network setting Call records Local Clock setting

Network and Configuration

Internet Connection Type Fixed IP, DHCP, PPPoE

LCD / Keypad UI Management Web (HTTP) Dimension (W x D x H) 262 x 230 x 95 mm

Operating Environment 0~40 Degree C, 5~95% humidity

Power Requirement 12 V DC EMC/EMI CE, FCC





ICF-1600-PA	Internet Video Conferencing Phone, PAL
ICF-1600-NT	Internet Video Conferencing Phone, NTSC

AVAILABLE MODULES

IPX-300 IPX-300W