

CAM-ISD48 Wall Mount Bracket – CAM-WM

Packet Content

Wall Mount	Wall Fix Screw x	Hex Screw x 3	Hexagon Wrench	Quick Installation
Bracket x 1	4		x 1	Guide x 1


■ Installation

Before assembling, please make sure you have read the CAM-ISD48 manual to Pre-assemble the CAM-ISD48 Bowl Module properly.

Mount the camera on wall

- 1. Take the wall-mount bracket, put it on the target place and fix it with the supplied wall fix screws (total 4 screws).
- 2. Take the cover-screw off the bracket, and remove the cover from this bracket.
- 3. Attach the bowl to the bracket and tight them together with hex screws.
- 4. Put the cables in the trench of bracket, and all connectors come out through the cable outlet. Then put the cover back and fix the cover with the screws removed at step 2





- 5. Locate the assembled piece onto the place the camera is to be mounted, and fix it on the surface completely with screws through the 4 holes on the bracket.
- Get the camera and plug it onto the base; watch for the direction of the connectors on camera and mounting base and be sure they are mated well. Then rotate the camera body counter-clockwise until it is completely locked.

Caution:

- Whiling fixing the camera, please make sure the operator is in a secured and safe area that will not fall from the install site or get injury by the objects around such as electric wire.
- 2. The equipments are heavy, make sure to install those equipments tightenly to prevent from falling and hurt the people below the cameras during and after the installation

