

UTM Content Security Gateway



The innovation of the Internet has created a tremendous worldwide opportunities for e-business and information sharing; however, it also brings network security issues. The request of information security becomes the primary concern for the enterprises. To fulfill the demand, PLANET introduces the UTM Content Security Gateway CS-2001, the next generation of the CS-2000, to support the enterprises build up the secure network protection. For further IP compatibility, it supports IPv6 as well.


The CS-2001 adopts Heuristics Analysis to filter spam emails and virus, and its auto-training system can increase the spam emails identification. The CS-2001 has built-in 500GB Hard Disk to store the spam email in quarantine. The Anti-Virus application has dual virus scan engines - Clam and Sophos to effectively detect viruses, worms and other threats from emails and Internet. Moreover, it helps the administrators to monitor the email status easily via email reports by Daily, Weekly, Monthly and Yearly.

Besides filtering spam and virus emails, the CS-2001 presents the IDP (Intrusion Detection and Prevention) and firewall functions to defense hackers and blaster attacks from Internet or Intranet. The comprehensive functions in one device provide enterprises security solutions for better secure environment than ever. The CS-2001 supports most of popular security features including Content Blocking to block specific URL, Scripts, IM/P2P program, Authentication, IPSec, PPTP VPN server/Client, SSL VPN, QoS, High Availability, Inbound Load-Balancing and etc. Furthermore, it provides higher performance with all Gigabit Ethernet interfaces which offer faster speeds for your network applications. The Gigabit user defined interfaces flexibly fulfill the network requirement nowadays, and the multiple WAN interfaces enable the CS-2001 to support Outbound / Inbound load balance and WAN fail-over features. As the result, the VPN not only can configure Trunk mode but also provide VPN fail-over and load balance features which is a VPN redundant mechanism to keep the VPN always alive.

APPLICATIONS

UTM Content Security Gateway

PLANET UTM Content Security Gateway, CS-2001, is a specially designed security gateway with virus and spam filtering features. As the gatekeeper of corporate security network, the CS-2001 prevents corporate intranet from being infected by virus and its network resource being occupied by useless spam emails. Furthermore, IDP, User Authentication and Content Filter features of the security gateway offer the corporate intranet highly secure protection. The CS-2001 also provides the IPSec, SSL VPN, and PPTP VPN solutions for secure data delivery via VPN tunnel.



Data Sheet



KEY FEATURES

ALL GIGABIT USER DEFINED INTERFACE

 The CS-2001 not only supports all Gigabit Ethernet interfaces to provide higher performance but is also able to be defined the interface role for your network environment.

IPV6

 IPv6 is designed to success the IPv4 version. The CS-2001 implements the new IP version for further compatibility of network environment.

ANTI-SPAM FILTERING

 Multiple defense layers (Spam Fingerprint, Blacklist & Whitelist, Bayesian Filtering, Spam Signature, Graylist, Checking sender account and IP address in RBL), and Heuristics Analysis help to block over 95% of spam mails. Customizable notification options and spam mail report are provided for the administrators. Varied actions to spam mails include Delete, Deliver, Forward and Store in the quarantine. It also has built-in auto-training system to improve the spam emails identification substantially.

ANTI-VIRUS PROTECTION

 Built-in dual virus scan engines can detect viruses, worms and other threats from email transfer and can scan mission-critical content protocols, SMTP and POP3 in real time to provide maximum protection. It provides customizable notification options and virus mail report for the administrators. Varied actions to virus mails include Delete, Deliver, Forward and Store in the quarantine.

ANTI-VIRUS FOR HTTP, FTP, P2P, IM, NETBIOS

• The CS-2001 can filter the virus from various protocols. The virus pattern can be updated automatically or manually.

VPN CONNECTIVITY

 The CS-2001 supports several VPN features -- IPSec VPN, SSL VPN and PPTP server/client. The VPN Tunnel with DES / 3DES / AES encryption and SHA-1 / MD5 authentication provides secure network traffic over public Internet. VPN Wizard helps the administrators to configure VPN settings easily.

SSL VPN

• SSL VPN allows users to easily establish VPN connections for transferring the data by SSL encryption via web browser without the need of any software or hardware installation.

VPN TRUNK

 VPN trunk function provides VPN load balance and VPN failover feature to keep the VPN connection more reliable.

CONTENT FILTERING

 The CS-2001 can block network connection based on URLs, Scripts (The Pop-up, Java Applet, cookies and Active X), P2P (eDonkey, Bit Torrent, WinMX and more), Instant Messaging (MSN, Yahoo Messenger, ICQ, QQ, Skype and Google Talk) and Download / Upload. If there are update versions of P2P or IM software in client side, the CS-2001 will detect the difference and update the Content Filtering pattern to renew the filtering mechanism.

IM RECORDING

 Built-in IM Recoding function can help you record and monitor the use of MSN and QQ messenger. This can prevent productivity losses from personal use and confidentiality breaches from information leaks.

IDP (INTRUSION DETECTION AND PREVENTION)

 Built-in IDP function can detect the intrusions and prevent the network from Hacker attacks, Anomaly Flow and Signatures from the Internet. The CS-2001 provides three kinds of the signatures to complete the intrusion detection system. Users can select to configure "Anomaly", "Pre-defined" and "Custom" according to the current environment request.

POLICY-BASED FIREWALL

 The built-in Policy-Based firewall prevents many well-known hacker attacks including SYN attack, ICMP flood, UDP flood, Ping of Death, and etc. The access control function specifies WAN or LAN users to use authenticated network services only on specified time.

005

 Network packets can be classified based on IP address, IP subnet and TCP/UDP port number and offer guarantee of maximum bandwidth with three levels of priority.

USER AUTHENTICATION

 Web-Based authentication allows users to be authenticated via web browser. User database can be configured on the CS-2001 and it also supports the authenticated database through external RADIUS, POP3 and LDAP server.

WAN BACKUP

 The CS-2001 can monitor each WAN link status and automatically activate backup links when a failure is detected. The detection is based on the configurable target Internet address

OUTBOUND LOAD BALANCING

 The network sessions are assigned based on the user configurable load balancing modes including "Auto", "Round-Robin", "By Traffic", "By Session" and "By Packet". Users can also configure IP or TCP/UDP type of traffic and assign which one of the two WAN ports for connection.

INBOUND LOAD BALANCING

 The Inbound Load Balancing is provided for enterprises internal server to reduce the server loading and system crash risks in order to improve the server working efficiency.

MULTIPLE NAT

 Multiple NAT allows local ports to be set in multiple subnets and connect to the Internet through different WAN IP addresses.

VLAN

 The CS-2001 provides IEEE 802.1Q Tagged VLAN and the VLAN groups which allow the administrator to install the network flexibly.

HIGH AVAILABILITY

 The CS-2001 provides the High Availability function and the redundant system to keep the network traffic active when the device crash down.



SPECIFICATION

Product UTM Content Security Gateway Model CS-2001 Hardware Ethernet 4 x Undefined Ethernet port 10/100/1000Base-T RJ-45, Auto-Negotiation, Auto MDI / MDI-X Console 1 x RS-232 (9600, 8, N, 1) Hard Disk 500 GB Hardware Watch-Dog Auto reboot when detecting system fail Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) Firewall Performance 1.6Gbps incoming and outgoing	
Hardware Ethernet	
Ethernet 4 x Undefined Ethernet port 10/100/1000Base-T RJ-45, Auto-Negotiation, Auto MDI / MDI-X Console 1 x RS-232 (9600, 8, N, 1) Hard Disk 500 GB Hardware Watch-Dog Auto reboot when detecting system fail Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Console 1 x RS-232 (9600, 8, N, 1) Hard Disk 500 GB Hardware Watch-Dog Auto reboot when detecting system fail Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Hard Disk 500 GB Auto reboot when detecting system fail Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Hardware Watch-Dog Auto reboot when detecting system fail Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Software Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Management Web (English, Traditional Chinese, Simplified Chinese) Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Operation Mode DMZ_Transparent, DMZ_NAT, NAT Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Routing Protocol Static Route, RIPv2, OSPF, BGP Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Concurrent Sessions 1,000,000 New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
New session per second 10,000 Email Capacity per Day (mail size 1098 bytes) 2,000,000	
Email Capacity per Day (mail size 1098 bytes) 2,000,000	
(mail size 1098 bytes) 2,000,000	
(mail size 1098 bytes)	
Firewall Performance 1.6Gbps incoming and outgoing	
SSL VPN Performance 80Mbps	
IPSec VPN Performance	
(With 3DES)	
■ Policy-Based access control	
Firewall Security Stateful Packet Inspection (SPI)	
■ NAT / NAPT	
■ Supports max. 64 multiple subnets	
Multiple subnet ■ VLAN id feature to assign multiple subnets	
■ VLAN trunk support	
VPN Tunnels	
(Connection/Configure) 200 / 1000	
■ IPSec, SSL VPN, PPTP server and client	
■ DES, 3DES and AES encrypting	
VPN Function	
■ SHA-1 / MD5 authentication algorithm ■ Remote pages VPN (Client to Site) and Site to Site VPN	
Remote access VPN (Client-to-Site) and Site to Site VPN	
QQ / MSN Account Manager	
IM Recording ■ Periodic Report Scheduling / Send report to e-mail	
■ IM Conversation logs and statistics chart	
■ URL Blocking	
■ Script Blocking (Popup, Java Applet, cookies and Active X)	
Content Filtering ■ IM blocking (MSN, Yahoo Messenger, ICQ, QQ, Skype, Google Talk and more)	
■ P2P blocking (eDonkey, Bit Torrent, WinMX and more)	
■ Download and Upload blocking	
■ Anti-Virus for HTTP, FTP, P2P, IM, NetBIOS	
■ Automatic or manual update virus and signature database	
IDP Anomaly: Syn Flood, UDP Flood, ICMP Flood and more	
■ Pre-defined: Backdoor, DDoS, DoS, Exploit, NetBIOS and Spyware	
■ Custom: User defined based on TCP, UDP, ICMP or IP protocol	
■ Yearly, Monthly, Weekly and Daily Report support	
■ Inbound scanning for external and internal Mail Server	
■ Support Spam Fingerprint, Bayesian, Signature, RBL and Graylist filtering, checking sender account	and IP
Anti Coam to filter the spam mail	
Anti-Spam ■ Black list and white list support auto training system	
■ Action of spam mail: Delete, Deliver to the recipient, forward to an account and store in quaranti	ne
■ Yearly, Monthly, Weekly and Daily Report support	
■ Policy-Based bandwidth management	
QoS ■ Guarantee and maximum bandwidth with 3 priority levels	
■ Classify traffics based on IP, IP subnet, TCP / UDP port	
■ Built-in user database with up to 500 entries	
User Authentication ■ Supports local database, RADIUS, POP3 and LDAP authentication	
■ Jupports local database, Indulos, FOEs and Loar addition	
■ Traffic Log Event Log and Connection Log	
Logs Traffic Log, Event Log and Connection Log Log can be caved from web, backup by a mail or system conver	
Log can be saved from web, backup by e-mail or syslog server	
Logs	





Statistics	WAN Ports traffic statistic and policies statistic with graph display
Others	■ Dynamic DNS
	■ NTP support
	■ Multiple Server load balancing
	■ Outbound / Inbound load balancing
	■ High Availability
	■ SNMP v1, v2, v3

ORDERING INFORMATION

CS-2001	UTM Content Security Gateway (Multiple WAN, LAN, DMZ)
---------	---

RELATED PRODUCTS

CS-1000	Multi-Homing Content Security Gateway
SG-4800	Gigabit SSL VPN Security Router
MH-3400	Gigabit Multi-Homing VPN Security Router
VRT-402N	802.11n Wireless VPN/Firewall Router
VRT-420N	802.11n Multi-Homing Broadband Router

Tel: 886-2-2219-9518

Email: sales@planet.com.tw