

User's Manual

HD Ultra-mini Bullet IR IP Camera

► ICA-3110



Copyright

Copyright © 2014 by PLANET Technology Corp. All rights reserved. No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise, without the prior written permission of PLANET.

PLANET makes no representations or warranties, either expressed or implied, with respect to the contents hereof and specifically disclaims any warranties, merchantability or fitness for any particular purpose. Any software described in this manual is sold or licensed "as is". Should the programs prove defective following their purchase, the buyer (and not PLANET, its distributor, or its dealer) assumes the entire cost of all necessary servicing, repair, and any incidental or consequential damages resulting from any defect in the software. Further, PLANET reserves the right to revise this publication and to make changes from time to time in the contents hereof without obligation to notify any person of such revision or changes.

All brand and product names mentioned in this manual are trademarks and/or registered trademarks of their respective holders.

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

1. Reorient or relocate the receiving antenna.
2. Increase the separation between the equipment and receiver.
3. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
4. Consult the dealer or an experienced radio technician for help.

FCC Caution

To assure continued compliance, for example, use only shielded interface cables when connecting to computer or peripheral devices. Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Federal Communication Commission (FCC) Radiation Exposure Statement

This equipment complies with FCC radiation exposure set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antenna shall not be less than 20 cm (8 inches) during normal operation.

Safety

This equipment is designed with the utmost care for the safety of those who install and use it. However, special attention must be paid to the dangers of electric shock and static electricity when working with electrical equipment. All guidelines of this and of the computer manufacture must therefore be allowed at all times to ensure the safe use of the equipment.

CE Mark Warning

This is a Class B product. In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

WEEE Regulation

To avoid the potential effects on the environment and human health as a result of the presence of hazardous substances in electrical and electronic equipment, end users of electrical and electronic equipment should understand the meaning of the crossed-out wheeled bin symbol. Do not dispose of WEEE as unsorted municipal waste; they should be collected separately.

Revision

User's Manual for PLANET HD Ultra-mini Bullet IR IP Camera
Model: ICA-3110
Rev: 1.00 (April.2014)
Part No. EM-ICA3110

Table of Contents

Chapter 1. Product Introduction	6
1.1 Package Contents	6
1.2 Overview	6
1.3 Features	9
1.4 Product Specifications	10
Chapter 2. Hardware Interface	12
2.1 Physical Descriptions	12
2.2 Hardware Installation	13
2.2.1 Installing camera with screws	13
2.2.2 Network Installation	13
2.3 Initial Utility Installation	14
2.4 Using UPnP of Windows XP or 7	18
2.4.1 Windows XP	18
2.4.2 Windows 7	22
2.5 Setting up ActiveX to use the Internet Camera	23
2.5.1 Internet Explorer 6 for Windows XP	23
2.5.2 Internet Explorer 7 for Windows XP	24
2.5.3 Internet Explorer 7 for Windows Vista	25
Chapter 3. Web-based Management	26
3.1. Introduction	26
3.2. Connecting to Internet Camera	26
3.3 Live Viewing	27
3.4 Configuration	29
3.5 System	29
3.5.1 System Information	29
3.5.2 User Management	31
3.5.3 System Update	32
3.6 Network	33
3.6.1 IP Setting	33
3.6.2 Advanced	36
3.6.3 PPPoE & DDNS	41
3.6.4 Mail & FTP & SAMBA	43
3.7 A/V Setting	44
3.7.1 Image Setting	44
3.7.2 Video Setting	46
3.7.3 Audio Setting	48
3.8 Event List	50
3.8.1 Event Setting	50
3.8.2 Schedule	51
3.8.3 I/O Setting	52
3.8.4 Log List	53
3.8.5 SD card	53
Appendix A: I/O Configuration	56
Appendix B: PING IP Address	59
Appendix C: 3GPP Access	60
Appendix D: PLANET DDNS Application	61
Appendix E: Configuring Port Forwarding Manually	63
Appendix F: Troubleshooting & Frequently Asked Questions	66


Appendix G: Micro SD Card Compatibility	70
---	----

Chapter 1. Product Introduction

1.1 Package Contents

The package should contain the following items:

- Camera unit x 1
- User's Manual CD x 1
- Quick Installation Guide x 1
- Stand Package x 1



Note

1. If any of the above items are missing, please contact your dealer immediately.
2. Using the power supply that is not the one included in the Internet Camera packet will cause damage and void the warranty for this product.

1.2 Overview

Superior Full HD Grade Video Quality

PLANET ICA-3110 PoE IP Camera provides high resolution images for round-the-clock surveillance over IP networks. It supports H.264 and JPEG compression formats and delivers excellent picture quality in Full HD resolutions at 25 frames per second (fps). It is perfect for remote and discreet monitoring of indoor areas such as home, small businesses, boutiques, restaurants, hotels, residences, etc.



Mini Design for Easy Installation

The ICA-3110 is an ultra lightweight IP camera in compact size, thus offering a quick and simple installation on the ceilings or walls inside of houses and buildings. Installation can be finished in less than 60 seconds.




Exceptional Image Quality

Together with powerful image processing attributes like Wide Dynamic Range (WDR) and Dimension Noise Reduction (DNR) technologies, the ICA-3110 is able to filter the intense backlight surrounding a subject and remove noises from video signal. The result is that an extremely clear and exquisite picture quality can be produced even under any challenging lighting conditions.



Advanced Event Management

The ICA-3110 supports a number of advanced features to enhance surveillance flexibility and event management capabilities. The advanced features include inputs/outputs for connecting to external devices such as door sensors and relays to activate light or closed doors.



Digital Input /Output

Full Surveillance during Day & Night Functionality

For a clear surveillance image both in the day and night, the ICA-3110 built-in 7 IR LEDs can offer IR distance of up to 5 meters. Its 720P resolution makes the image still clear even at night. The ICA-3110 also is equipped with ICR 2.8mm / F1.8, and auto-iris function which can automatically adjust the amount of light that passes through the lens. Thus, the ICA-3110 is able to maintain clear images 24 hours a day.



Flexible Installation and Power Functionality

The ICA-3110 incorporates IEEE 802.3af Power over Ethernet technology and can be powered from a PoE Switch via the network, which eliminates the need for power cables and reduces installation costs. The ICA-3110 is ONVIF-compliant and therefore interoperable with other brands in the market, greatly supporting users to integrate with their existing surveillance network. In addition, the ICA-3110 includes 64-CH central management software for efficient monitoring. The ICA-3110 is indisputably the top choice for reliable and high performance surveillance.



1.3 Features

➤ **Camera**

- 1/4" progressive scan CMOS sensor
- 0.2 lux minimum illumination at F1.8
- Maximum resolution 1920 x 800
- Easily-recessed mount design
- Convenient nano-design blends in nicely with any surrounding
- Built-in 7 IR LEDs for IR monitoring distance of up to 5 meters

➤ **Video / Audio**

- H.264 and M-JPEG video compression simultaneously
- Simultaneous multi-H.264 streams support
- H.264 main profile and baseline profile
- Max. resolution of 1 mega-pixel at 30fps
- DNR to improve picture quality at low lux
- WDR Enhancement function strengthens visibility under extremely bright or dark environments
- 2-way audio support with enhanced audio quality

➤ **Network and Configuration**

- Compliant with IEEE 802.3af PoE interface for flexible deployment
- Auto MDI/MDI-X supported
- Supports IPv6 in addition to IPv4
- Built-in Samba client for NAS
- RTSP / UPnP / 3GPP / HTTPS protocols selectable
- 3GPP for 3G mobile remote applications
- Access anytime & anywhere for PLANET easy DDNS

➤ **Easy Installation & Management**

- ONVIF compliant for interoperability
- Tamper and motion detection for unauthorized changes
- Micro SD card local video recording supported
- Easy configuration and management via Windows-based utility or web interface
- Cam Viewer 3 central management software supported
- Digital Input/Output for integration with sensors and alarms

1.4 Product Specifications


Model	ICA-3110
Camera	
Image Device	1/4" progressive scan CMOS sensor
Lens	Fixed lens 2.8mm, F1.8 Angle of view : horizontal: 77.78 degrees / vertical: 49.55 degrees
Min Illuminator	Color : 0.2 Lux (AGC ON) B / W: 0.1 Lux (AGC ON)
Electronic Shutter	Auto, 1 / 5 ~ 1 / 10,000 sec
Effective Pixels	1920 x 800 pixels
LEDs	7 LEDs, 850nm
IR distance	5 meters
Video	
Video Compression	H.264 / M-JPEG
Video Resolutions	H.264: 1280 x 800 / 1280 x 720 / 640 x 480 / 320 x 240 / 176 x 144 M-JPEG: 1280 x 800 / 1280 x 720 / 640 x 480 / 320 x 240 / 176 x 144
Frame Rate	Up to 30fps for all resolution
Image Setting	Brightness, Contrast, Hue, Saturation, Sharpness, AGC, Shutter Time, Sense-up, D-WDR, Anti Fog, Lens Distortion Correction, Flip, Mirror, Day&Night adjustable, Red Gain and Blue Gain, Denoise
Streaming	Simultaneously multi-profile streaming M-JPEG streaming over HTTP Supports 3GPP mobile surveillance Controllable frame rate and bandwidth Constant and variable bit rate (H.264)
Audio	
Audio Streaming	2-way audio
Audio Compression	RTSP: G.711 64kbps, G.726 32, 24kbps 3GPP: AMR
Microphone	Built-in microphone input
Audio Output	3.5mm phone jack
Network and Configuration	
Network Standard	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX
Protocol	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X Port-based authentication for network protection, QoS/DSCP
Users	10 clients on-line monitoring at the same time
System Integration	
Application Programming Interface	Open SDK/API for software integration ONVIF Compliant
Alarm Triggers	Intelligent video motion detection and external input


	3-zone video motion detection
Alarm Events	File upload via FTP, Samba, SD card or email External output activation
General	
Power Requirements	IEEE 802.3af Class 3
Power Consumption	PoE Max: 2.88W (IR ON); 2.23W (IR Off)
Operating Temperature	0 ~ 45 degrees C
Operating Humidity	10 ~ 95% (non-condensing)
Weight	135g
Dimensions (Φ x L)	44 x 95 mm
Emission	CE, FCC
Connectors	10/100 Mbps Ethernet, RJ-45 Terminal block for 1 alarm input, 1 output and factory default reset Micro SD/SDHC card (Max. 32GB, Class 6)

Chapter 2. Hardware Interface

2.1 Physical Descriptions

Real Panel



Interface	Description
LAN(PoE)	The LAN socket is a RJ-45 connector for connections to 10Base-T Ethernet or 100Base-TX Fast Ethernet cabling. This Ethernet port built N-Way protocol can detect or negotiate the transmission speed of the network automatically. Please use Category 5 cable to connect the Network Camera to a 100Mbps Fast Ethernet network switch or hub.
Micro-SD	User can insert a micro SD card into this slot for event recording.
Factory Default Reset	<p>This button is hidden in the pinhole. This button is used to restore the all factory default settings. Sometimes restarting the camera will make the system back to a normal state. If the system still got problems after restart, user can restore the factory default settings and install it again. To restore the device, please follow the steps below:</p> <ol style="list-style-type: none"> 1. Unplug the power jack, then press and hold the reset button. 2. Power on the camera. Don't release the button during the system booting. 3. It will take around 30 seconds to boot the camera. 4. Release the button (remove the pin from the reset hole). The camera should now be back to factory default. 5. Login the camera using the default IP (http://192.168.0.20), and username (admin), password (admin). <div>  <p>Restoring the factory default setting will lose all the previous settings including IP address forever. User needs to run the IPInstaller program to search the device and configure it to let the device work properly again.</p> </div>
DI/DO	Connect the power and the Ethernet with the camera. The

	four-colored wires are used for I/O connection. About I/ O setting.	
	Name	Function
	GND	GND
	DI	Digital signal input
	DO	Digital signal output
Audio Out	Audio-out jack allows this device to output audio signal.	


2.2 Hardware Installation

2.2.1 Installing camera with screws

1. Attach the Camera to the stand included.

2. Place the Camera on the table or fix it onto the ceiling or wall


Use three screws to fix the Network Camera onto the ceiling or wall. You could also put the Network Camera on the table directly.



2.2.2 Network Installation

1. Connecting an Ethernet cable


Connect the LAN cable on the camera to the network device (hub or switch).



If there is an IEEE802.3af PoE switch in your network, you can connect the camera LAN cable to this PoE switch to obtain power. The power adapter is unnecessary when Internet camera is connected to a PoE switch.

2. Attach the power supply

Plug in power adapter and connect to power source. After power on, the camera will start to operate.




Note

1. Only use the power adapter supplied with Internet camera; otherwise, the product may be damaged.
2. The power adapter is unnecessary when Internet camera is connected to a PoE switch. Otherwise, the product may be damaged when Internet camera is connected to a PoE switch and power adapter simultaneously.

3. PoE (Power over Ethernet)


Power over Ethernet (PoE) is a technology that integrates power into a standard LAN infrastructure. It enables power to be provided to the network device, such as an IP phone or a network camera, using the same cable as that used for network connection. It eliminates the need for power outlets at the camera locations and enables easier application of uninterruptible power supplies (UPS) to ensure 24 hours a day, 7 days a week operation.



2.3 Initial Utility Installation

This chapter shows how to quickly set up your H.264 camera. The camera is with the default settings. However to help you find the networked camera quickly the windows utility PLANET IP Installer can search the cameras in the network that will help you to configure some basic settings before you start advanced management and monitoring.

1. Insert the bundled CD into the CD-ROM drive to launch the auto-run program. Once completed, a welcome menu screen will appear.
2. Click the "IPinstaller" hyperlink; you will see the dialog box below.




Note

If the welcome screen does not appear, click "Start" at the taskbar. Then, select "Run" and type "D:\Utility\PLANETIPInstaller\PLANETIPInstaller.exe", assuming D is your CD-ROM drive.

3. OS: Windows XP SP2 or above. If the following “**Windows Security Alert**” pops up, please click “Unblock”.




4. The GUI of IP Installer is as follows (Default IP: 192.168.0.20).




- (1) IP Installer will search all IP cameras connected to LAN. The user can click “**Search Device**” to search again.
- (2) Click one of IP cameras listed on the left side of IP Installer, then the network configuration of that IP Camera will be listed on the right side. If parameters change, click on “**Submit**”. Then, the network configuration will be changed. Just click “**OK**” to reboot



- (3) Please make sure the subnet of PC IP address and IP CAM IP address are the same.
IP CAM IP address: **192.168.0.20**
PC IP address: **192.168.0.100**
- (4) Different Subnets:
IP CAM IP address: **192.168.0.20**
PC IP address: **192.168.1.100**
- (5) To Change PC IP addresses:
Control Panel→Network Connections→Local Area Connection Properties→Internet Protocol (TCP/IP) →Properties
Please make sure your IP Camera and PC have the same Subnet. If not, please change IP Camera IP subnet or PC IP subnet accordingly.



- (6) A quick way to access remote monitoring is to left-click the mouse twice on a selected IP camera listed on "Device list" of PLANET IP Installer. An IE browser will be opened.
- (7) Then, please key in the default User Name: "**admin**" and Password "**admin**" in the following message box.




- (8) If the user name and password are input correctly, the following web page will be displayed.



2.4 Using UPnP of Windows XP or 7


2.4.1 Windows XP

UPnP™ is short for Universal Plug and Play, which is a networking architecture that provides compatibility among networking equipment, software, and peripherals. This device is an UPnP enabled device. If the operating system, Windows XP, of your PC is UPnP enabled, the device will be very easy to configure. Use the following steps to enable UPnP settings only if your operating system of PC is running Windows XP.




Please note that MS Windows 2000 does not support UPnP feature.


Go to **Start > Settings**, and Click **Control Panel**.



The “**Control Panel**” will display on the screen and double-click “**Add or Remove Programs**” to continue.




The “Add or Remove Programs” will display on the screen and click **Add/Remove Windows Components** to continue.



The following screen will appear, select “**Networking Services**” and click “**Details**” to continue.




The “Networking Services” will display on the screen, select “**Universal Plug and Play**” and click “**OK**” to continue.



Please click “**Next**” to continue.




The program will start installing the UPnP automatically. You will see the pop-up screen below. Please wait while Setup configures the components.



Please click **"Finish"** to complete the UPnP installation





Double-click “**My Network Places**” on the desktop, and the “My Network Places” will display on the screen. Double-click the UPnP icon with Internet Camera to view your device in an internet browser.





2.4.2 Windows 7

Go to **Start > Control Panel > Network and Internet > Network and Sharing Center**, if network discovery is off; click the arrow button  to expand the section.

Click Turn on network discovery, and then click Apply.  If you are prompted for an administrator password or confirmation, type the password or provide confirmation.





2.5 Setting up ActiveX to use the Internet Camera


The Internet Camera web pages communicate with the Internet Camera using an ActiveX control. The ActiveX control must be downloaded from the Internet Camera and installed on your PC. Your Internet Explorer security settings must allow for the web page to work correctly. To use the Internet Camera, user must set up his IE browser as follows:

2.5.1 Internet Explorer 6 for Windows XP

From your IE browse → "Tools" → "Internet Options..." → "Security" → "Custom Level...", please set up your "Settings" as follows:

Set the first 3 items

- Download the signed ActiveX controls
- Download the unsigned ActiveX controls
- Initialize and script the ActiveX controls not masked as safe to Prompt




By now, you have finished your entire PC configuration for Internet Camera.

2.5.2 Internet Explorer 7 for Windows XP

From your IE browse → "Tools" → "Internet Options..." → "Security" → "Custom Level...", please set up your "Settings" as follows:

Set the first 3 items

- Allows previously unused ActiveX control to run...
- Allows Scriptlets
- Automatic prompting for ActiveX controls





By now, you have finished your entire PC configuration for Internet Camera.

2.5.3 Internet Explorer 7 for Windows Vista



From your IE browse → "Tools" ("Internet Options..." ("Security" ("Internet" ("Custom Level...", please set up your "Settings" as follows:

- Enable "Automatic prompting for ActiveX controls"
- Prompt "Initialize and script active controls not marked...."



From your IE browse → "Tools" → "Internet Options..." ("Security" ("Trusted Sites" ("Custom Level...", please set up your "Settings" as follows:

- Enable "Automatic prompting for ActiveX controls"
- Prompt "Initialize and script active controls not marked...."



By now, you have finished your entire PC configuration for Internet Camera.

Chapter 3. Web-based Management

This chapter provides setup details of the Internet Camera's Web-based Interface.

3.1. Introduction

The Internet Camera can be configured with your Web Browser. Before configuring, please make sure your PC is under the same IP segment as Internet Camera.


3.2. Connecting to Internet Camera

A. Use the following procedures to establish a connection from your PC to the Internet Camera.


B. Once connected, you can add the camera to your Browser's Favorites or Bookmarks.

Start the web browser on the computer and type the IP address of the camera.

The Default IP: "<http://192.168.0.20/>"




The login window of Internet Camera will appear,
Default login **username** and **password** is: **admin** and **admin**




If the User Name and Password have been changed with PLANET IP Installer, please enter the new User Name and Password here.

Web browser may display the "**Security Warning**" window, select "**Yes**" to install and run the ActiveX control into your PC.



After the ActiveX control is installed and run, the first image will be displayed.





If you log in the camera as an ordinary user, setting function will be not available. If you log in the camera as the administrator, you can perform all the settings provided within the device.

3.3 Live Viewing


Start-up screen will be as follows no matter you are an ordinary user or an administrator.



(1)Configure	 Get into the menu for configuration.
(2)Snapshot	 Video Snapshot
(3)Status Bar	Show system time, video resolution, and video refreshing rate
(4)Screen Size	Select video screen “default, 1/2x, 1x, 2x” for view currently camera screen size
(5)Streaming Select	Select video streaming source (When streaming 2 setting in 『Video Setting』 is closed, this function will not display)
(6) Chatting	Please check this item to execute two-way audio function, then connect speaker to camera so that user can hear the voice from PC.
(7) Online Visitor	Shows how many people connect to this IP camera
(8) Relay Control	Control the relay which is connected to this camera

Double-click the video and it will change to full screen mode. Press “**Esc**” or double-click the video again, it will change back to normal mode. Right-click the mouse on the video, it will show a pop-up menu.

Snapshot
Record Start
Full Screen
Zoom
FrameBuffmSec ▶




Snapshot	Save a JPEG picture.
Record Start	Record the video in the local PC. It will ask you where to save the video. To stop recording, right-click the mouse again. Select “ Record Stop ”. The video format is AVI. Use Microsoft Media Player to play the recorded file.
Full Screen	Full-screen mode.


ZOOM	Enable zoom-in and zoom-out functions. Select “ Enable digital zoom ” option first within the pop-up dialogue box and then drag and drop the bar to adjust the zoom factors.
FrameBufferSec	Build a buffer to accumulate several video frames and play at a regular interval. This function can make video smooth-going when the Network speed is slow and lag. If you select “100”, the interval between every frame is fixed to 100 mSec. The slower the Network is, the bigger value should be selected. The default value is null.


3.4 Configuration



Click  to get into the administration page.



Click  to go back to the live video page.



System Information

Server Information

MAC Address: 00:30:4F:24:D2:88

Server Name: PLANET IP Camera ☐ Status Bar

LED Indicator: ☒ ON ☐ OFF

Language: ☒ English ☐ 繁體中文 ☐ 简体中文 ☐ French
☐ Russian ☐ Italian ☐ Spanish ☐ German
☐ Portuguese ☐ Polish ☐ Japanese

OSD Setting

Time Stamp: ☒ Enabled ☐ Disabled

Position: ☒ Top-Left ☐ Top-Right ☐ Bottom-Left ☐ Bottom-Right

Text: ☒ Enabled ☐ Disabled

OSD Display [Text Edit](#)

Time Setting

Server Time: 2013/6/18 15:15:12 Time Zone: GMT+08:00

Date Format: ☒ yy/mm/dd ☐ mm/dd/yy ☐ dd/mm/yy

Time Zone: GMT+08:00

☐ Enable Daylight Saving:

☐ NTP:

NTP Server: pool.ntp.org

Update: 6 Hour

Time Shift: 0 Minutes [-1440..1440]

☐ Synchronize with PC's time

Date: 2013/6/18

Time: 15:14:21

☐ Manual

Date: 2013/6/18

Time: 15:14:18



☒ The date and time remain the same

[Apply](#)


3.5 System

3.5.1 System Information

1. Server Information: Set up the camera name, select language, and set up the camera time.

(1)Configure	 Get into the menu for configuration.
(2)Snapshot	 Video Snapshot
(3)Status Bar	Show system time, video resolution, and video refreshing rate
(4)Screen Size	Select video screen “default, 1/2x, 1x, 2x” for view currently camera screen size
(5)Streaming Select	Select video streaming source (When streaming 2 setting in 『Video Setting』 is closed, this function will not display)
(6) Chatting	Please check this item to execute two-way audio function, then connect speaker to camera so that user can hear the voice from PC.
(7) Online Visitor	Shows how many people connect to this IP camera
(8) Relay Control	Control the relay which is connected to this camera

Double-click the video and it will change to full screen mode. Press “**Esc**” or double-click the video again, it will change back to normal mode. Right-click the mouse on the video, it will show a pop-up menu.



Snapshot	Save a JPEG picture.
Record Start	Record the video in the local PC. It will ask you where to save the video. To stop recording, right-click the mouse again. Select “ Record Stop ”. The video format is AVI. Use Microsoft Media Player to play the recorded file.
Full Screen	Full-screen mode.

3. Server time setting : Select options to set up time - “NTP”, “Synchronize with PC’s time”, “Manual”, “The date and time remain the same”.

Time Setting

Server Time: 2013/6/18 15:25:23 Time Zone: GMT+08:00

Date Format: ☒ yy/mm/dd ☐ mm/dd/yy ☐ dd/mm/yy

Time Zone:

☐ Enable Daylight Saving:

☐ NTP :

NTP Server :

Update : Hour

Time Shift : Minutes [-1440..1440]

☐ Synchronize with PC's time

Date :

Time :

☐ Manual

Date :

Time :

☒ The date and time remain the same

3.5.2 User Management

IP camera supports three different users -- administrator, general user, and anonymous user.

User Management

Anonymous User Login

☐ YES ☒ NO [Setting](#)

Add User

Username:

Password:

Confirm:

[Add/Set](#)

User List

Username	User Group	Modify	Remove
admin	Administrator	Edit	-----

Anonymous User Login	Yes : Allow anonymous login No : Need user name & password to access this IP camera
Add user	Type the user name and password, and then click “Add/Set”.

Click “edit” or “delete” to modify the user

3.5.3 System Update

Firmware Upgrade	To update the firmware online, click " Browse... " to select the firmware. Then click "Upgrade" to proceed.
Reboot System	Re-start the IP camera.
Factory default	Delete all the settings in this IP camera. (Not include IP address)
Setting Management	User may download the current setting to PC, or upgrade from previous saved setting.

Setting download:

Right-click the mouse button on Setting Download → Select "**Save AS...**" to save current IP CAM setting in PC → Select saving directory → Save

Upgrade from previous setting:

Browse → search previous setting → open → upgrade → Setting update confirm → click [index.html](#) to return to main page

3.6 Network

3.6.1 IP Setting

IP camera supports DHCP and static IP.

IP Setting	
IP Assignment	
<input type="radio"/> DHCP	
<input checked="" type="radio"/> Static	
IP Address:	<input type="text" value="210.66.155.81"/>
Subnet Mask:	<input type="text" value="255.255.255.224"/>
Gateway:	<input type="text" value="210.66.155.94"/>
DHIS 0:	<input type="text" value="168.95.1.1"/>
DHIS 1:	<input type="text" value="8.8.8.8"/>
IPv6 Assignment	
<input checked="" type="checkbox"/> IPv6 Enabled:	
<input type="checkbox"/> Manually setup the IPv6 address:	
DHCPv6:	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled
Port Assignment	
Web Page Port:	<input type="text" value="80"/>
HTTPS Port:	<input type="text" value="443"/>
UPnP	
UPnP:	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled
UPnP Port Forwarding:	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled
External Web Port:	<input type="text" value="80"/>
External HTTPS Port:	<input type="text" value="443"/>
External RTSP Port:	<input type="text" value="554"/>


RTSP Setting			
RTSP Server:	<input checked="" type="radio"/> Enabled	<input type="radio"/> Disabled	
RTSP Authentication:	Disable ▼		
RTSP Port :	554		
RTP Start Port:	5000		[1024..9997]
RTP End port:	9000		[1027..10000]
Multicast Setting (Based on the RTSP Server)			
Streaming 1:			
IP Address:	234.5.6.78		[224.3.1.0 ~ 239.255.255.255]
Port:	6000		[1 ~ 65535]
TTL:	15		[1 ~ 255]
Streaming 2:			
IP Address:	234.5.6.79		[224.3.1.0 ~ 239.255.255.255]
Port:	6001		[1 ~ 65535]
TTL:	15		[1 ~ 255]
ONVIF			
ONVIF:	<input checked="" type="radio"/> V2.20	<input type="radio"/> v1.01	<input type="radio"/> Disabled
Security:	<input type="radio"/> Enabled	<input checked="" type="radio"/> Disabled	
RTSP Keepalive:	<input checked="" type="radio"/> Enabled	<input type="radio"/> Disabled	
Bonjour			
Bonjour:	<input type="radio"/> Enabled	<input checked="" type="radio"/> Disabled	
Bonjour Name:	IP_Camera		@00:30:4F:26:8E:21
LLTD (Link Layer Topology Discovery)			
LLTD:	<input checked="" type="radio"/> Enabled	<input type="radio"/> Disabled	

DHCP	Using DHCP, IP camera will get all the network parameters automatically.
Static IP	Please type in IP address, subnet mask, gateway, and DNS manually.
IPv6 Assignment	IPv6 is a newer numbering system that provides a much larger address pool than IPv4, which accounts for most of today's Internet traffic. You can set up IPv6 manually by keying in Address, Gateway, and DNS, or enabling DHCP to assign the IP automatically.
Port Assignment	User may need to assign a different port to avoid conflict when setting up IP assignment. (1) Web Page Port: setup web page connecting port and video transmitting port (Default: 80) (2) RTSP Port: setup port for RTSP transmitting (Default: 554) (3) RTP Start and End Port: in RTSP mode, you may use TCP and UDP for connecting. TCP connection uses RTSP Port (554). UDP connection uses RTP Start and End Port.
UPnP	This IP camera supports UPnP. If this service is enabled on your computer, the camera will automatically be detected and a new icon will be added to "My Network Places." Note: UPnP must be enabled on your computer.
UPnP Port Forwarding	When the camera is installed under a router, enable UPnP Port Forwarding to let the router open ports so that the video streams can be sent out from a LAN. Set Web Port, Http Port, and RTSP port, and make sure your router supports UPnPPTM

	and the function has been activated.
RTSP Server	enable or disable RTSP server
RTSP Authentication	<p>"Disable" means everyone who knows your camera IP Address can link to your camera via RTSP. No username and password are required.</p> <p>Under "Basic" and "Digest" authentication mode, the camera asks the user to give username and password before allows accessing. The password is transmitted as clear text under basic mode, which provides a lower level of security than under digest mode.</p> <p>Make sure your media player supports the authentication schemes</p>
RTSP port	<p>RTSP Port: setup port for RTSP transmitting (Default: 554)</p> <p>RTSP Start and End Port: in RTSP mode, you may use TCP and UDP for connecting. TCP connection uses RTSP Port (554). UDP connection uses RTSP Start and End Port.</p>
Multicast Setting (Based on the RTSP Server)	<p>Multicast is a bandwidth conservation technology. This function allows several users to share the same packet sent from IP camera. To use Multicast, appoint IP Address and port here. TTL means the life time of packet, The larger the value is, and the more users can receive the packet.</p> <p>To use Multicast, be sure to enable the function "Force Multicast RTP via RTSP" in your media player. Then key in the RTSP path of your camera: "rtsp://(IP address)/" to receive the multicast.</p>
ONVIF	<p>The IP camera supports ONVIF v1.01 / v1.02 / v2.10 standard for to integration.</p> <p>Under ONVIF connection, the video will be transmitted by RTSP. Be sure to enable the RTSP server in IP setting, or you're not able to receive the video via ONVIF.</p>
RTSP Keepalive	When the function is enabled, the camera checks once in a while if the user who links to the camera via ONVIF still keeps connecting. If the connection had been broken, the camera stop transmitting video to user.
Bonjour	<p>This function enables MAC systems to link to this IP camera. Key in the name here.</p> <p>The web browser "Safari" also has Bonjour function. Tick "Include Bonjour" in the bookmark setting, and you can see the IP camera appearing under the bonjour category. Click the icon to connect the IP camera.</p>
LLTD	<p>If your PC supports LLTD, enable this function then you can check the connection status, properties, and device position (like IP address) of this IP Camera in the network map.</p> <p>In the computer running Windows Vista or Windows 7, you can find LLTD through the path:</p> <p>Call out the Control Panel → Network and Internet → Network and Sharing Center → Click "See full map"</p>

3.6.2 Advanced

Https(Hypertext Transfer Protocol Secure)



HTTPS Setting

Created Request

Subject: C=TW , ST= , L= , O= , OU= , CN=

Date: 2012/Oct/23 19:08:33

[Content](#) [Remove](#)

Installed Certificate

Subject: C=TW , ST= , L= , O= , OU= , CN=

Date: Mar 14 08:45:42 2038 GMT

[Content](#) [Remove](#)

Connection Types

HTTP & HTTPS ▼


HTTP

HTTPS

HTTP & HTTPS

Https can help protect streaming data transmission over the internet on the higher security level. You can select the connection type. "Https" means user cannot connect the camera via Http protocol. The Https path will be: "https://(IP address)/". If you select "Http & Https", both the Http and Https path can be used to access the camera.

Remove the existing setting: Before setting new request, please remove old secure identification. Select "Http" connection type and click "Remove".



Https Setting

Created Request

Subject: C=TW , ST= , L= , O= , OU= , CN=

Date: 2011/Sep/23 10:04:17

[Content](#) [Remove](#)

Installed Certificate

Subject: C=TW , ST= , L= , O= , OU= , CN=


Date: Apr 23 09:05:24 2011 GMT

[Content](#) [Remove](#)

Connection Types

Http ▼

Created Request: Setting the secure identification and apply it



Https Setting

Create Request

Country:

State or province:

Locality:

Organization:

Organizational Unit:

Common Name:

[Apply](#)

There are two ways to set Certificate- Install Signed Certificate or Create Self-Signed Certificate.




The screenshot shows a web interface with two sections. The top section, 'Install Signed Certificate', has a text input for 'Signed Certificate:' and an 'Apply' button. The bottom section, 'Create Self-Signed Certificate', has input fields for 'Country:', 'State or province:', 'Locality:', 'Organization:', 'Organizational Unit:', 'Common Name:', and 'Validity:' (with a 'Days' label). It also has an 'Apply' button.

SNMP (Simple Network Management Protocol)

SNMP provides a simple framework for administering networked hardware. To manage the IP camera, you have to prepare an MIB browser or similar tools first. SNMPv1, SNMPv2c, and SNMPv3 can be enabled simultaneously.

SNMPv1 and SNMPv2c:




The screenshot shows the 'SNMP Setting' section. It has a header 'SNMP' and a sub-header 'SNMP Setting'. Below the sub-header, there are checkboxes for 'SNMPv1' and 'SNMPv2c'. The 'SNMPv2c' checkbox is checked. Below the checkboxes, there are two text input fields: 'Write Community:' with the value 'write' and 'Read Community:' with the value 'public'.

The term "Community name" in SNMPv1 and SNMPv2c can be roughly regarded as key. The person who has the community name has the authority to read or edit the information of IP camera via SNMP.

Tick the box to enable SNMPv1 or SNMPv2c protocol, and specify the community name for write (read and write) and read (read-only). The user who use read community name to access the IP camera cannot modify any data of this camera.

SNMPv3:



The screenshot shows the 'SNMPv3' section. It has a checkbox for 'SNMPv3' which is checked. Below the checkbox, there are two sets of configuration fields. The first set is for 'Write Security Name:' with the value 'write'. The second set is for 'Read Security Name:' with the value 'public'. Each set includes fields for 'Authentication Type:' (with radio buttons for MD5 and SHA), 'Authentication Password:', 'Encryption Type:' (with radio buttons for DES and AES), and 'Encryption Password:'.

For data security reason, the authentication and encryption assurances are added when developing SNMPv3. The user has to give not only the security name (the same as "community name" in v1&v2c, or sometimes we call it "context name") but the password in order to access the IP camera. Please set security name, authentication type, authentication password, encryption type, encryption password of write and read respectively. The password must be 8~64 bits in length.

Different from SNMPv1 and v2c, the user have to create an account when using SNMPv3. In the account parameters, key in the security name and password you set in the camera to get accessing.

SNMPv1/SNMPv2 Trap:

<input checked="" type="checkbox"/> SNMPv1/v2c Trap	
Trap Address:	<input type="text"/>
Trap Community:	<input type="text" value="public"/>
Trap Event:	<input type="checkbox"/> Cold Start <input type="checkbox"/> Setting Changed <input type="checkbox"/> Network Disconnected <input type="checkbox"/> V3 Authentication Failed <input type="checkbox"/> SDCard Insert/Remove

Trap is a mechanism that allows the managed device to send messages to manager instead of waiting passively for polling from the manager. Specify the trap event. When those events happen, the camera will send the ring message to the Trap Address, which is usually the manager's IP address. Trap Community means the community that can receive the trap message.

- Cold Start: The camera starts up or reboots.
- Setting changed: The SNMP setting is changed.
- Network Disconnected: The network connection was broken down. (The camera will send trap messages after the network being connected again)
- V3 Authentication Failed: A SNMPv3 user account tries to get authentication but failed. (Due to incorrect password or community)
- SD Insert / Remove: A Micro SD card is inserted or removed.

Access List

IP FILTER

IP Address Filter Setting

☒ Enable ip address filter

IPv4 Setting:

☒ allow ☐ deny

single address:

IPv4 List:

No.	IP Address	Filter	Action
1			<input type="button" value="remove"/>
2			<input type="button" value="remove"/>
3			<input type="button" value="remove"/>
4			<input type="button" value="remove"/>
5			<input type="button" value="remove"/>
6			<input type="button" value="remove"/>
7			<input type="button" value="remove"/>
8			<input type="button" value="remove"/>
9			<input type="button" value="remove"/>
10			<input type="button" value="remove"/>

☐ Allow admin ip address always access this device

Admin ip address:

You can deny an IP address or a range of IP address so that they cannot access the IP camera. Tick the "enable" box, key in the IP address you want to deny, select "deny" then click "Add" to add it to the list.

You can also choose to deny a range of IP addresses but allow one or several of them. Take the picture above for example, IP address 192.168.50.151~161 is not allowed to connect to the camera, but only 192.168.50.159 can access.



In the list "allow" condition must be ranked before "deny" condition.

For example, if we exchange the sequence, set "Deny: 192.168.50.151~192.168.50.161" for the first item and "Allow: 192.168.50.159" for the second item in the list, the IP "192.168.50.159" turns out to be denied by the camera because the "deny" condition has the priority according to our ranking way.

QoS/DSCP (Quality of Server/Differentiated Services Code-point)

QoS/DSCP

QoS/DSCP Setting

☒ Enable QoS/DSCP

Live Stream: (0~63)

Event / Alarm: (0~63)


Management: (0~63)

DSCP specifies a simple mechanism for classifying and managing network traffic and provide QoS on IP networks. DSCP is a 6-bit in the IP header for packet classification purpose. The number 0~63 for Live Stream, Event / Alarm, and Management represent the ratio that the

bandwidth is divided. For example, if you set 5, 10, and 20 for the three items, then the bandwidth of the three items is 5:10:20. There is no difference between setting "0, 0, 0" or "63, 63, 63" because under these two settings, the three items will get equal bandwidth (1/3).

The three stream control protocols are as follows:

- Live Stream (Video and audio): RTP / RTSP
- Event / Alarm : FTP / SMTP / SAMBA / SIP
- Management: HTTPS / HTTP / SNMP



The "Management" stream handles both the live view and the setting area of the web page on which the data is transferred via http/https protocol. If you prefer to distribute more bandwidth when using the web browser to access the camera, please adjust the Management stream.

IEEE 802.1x

IEEE 802.1x/EAP-TLS

IEEE 802.1x Setting

☐ Enable IEEE 802.1x
 Eapol version:
 Identity:
 Private key password:

☒ v1
 ☐ v2

CA certificate:

Status:

Client certificate:

Status:

Client private key:

Status:

IEEE 802.1x is an IEEE standard for port-based Network Access Control. It provides an authentication mechanism to device wishing to attach to a LAN or WLAN.

The EAPOL protocol supports service identification and optional point to point encryption over the local LAN segment.

Please check what version of the authenticator and authentication server support. This camera supports EAP-TLS method. Please enter ID and password issued by the CA, and then upload related certificates.

3.6.3 PPPoE & DDNS

PPPoE & DDNS

PPPoE Setting

☐ Enabled ☒ Disabled

Username:

Password:

Send mail after PPPoE dialed

☐ Enabled

Subject:

DDNS Setting

☒ Enabled ☐ Disabled

Provider:

Username:

Schedule Update: Minutes

State

Idle

Note:

1. Schedule Update: Depends on the input time of Schedule Update, it will update DDNS's web site automatically. The time range is from 5 to 5000 minutes.
*0: It will not update.
2. dyndns.org & 3322.org: Update once per day is recommended (1440 minutes per day). If updated too frequently, it will be blocked.

PPPoE: Stands for Point to Point Protocol over Ethernet

A standard builds on Ethernet and Point-to-Point network protocol. It allows Internet camera to connect to Internet with xDSL or cable connection; it can dial up your ISP and get a dynamic IP address. For more PPPoE and Internet configuration, please consult your ISP.

It can directly connect to the xDSL; however, it should be set up on a LAN environment to program the PPPoE information first, and then connect to the xDSL modem. Power on again, then the device will dial on to the ISP connection to the WAN through the xDSL modem.

The procedures are:

- (1) Select **"Enabled"** to use PPPoE.
- (2) Key-in username and password for the ADSL connection.
- (3) Send mail after dialing : When connected to the Internet, it will send a mail to a specific mail account. For the mail setting, please refer to **"Mail and FTP"** settings.

DDNS: Stands for Dynamic Domain Name Server

The device supports DDNS. If your device is connected to xDSL directly, you might need this feature. However, if your device is behind a NAT router, you will not need to enable this feature. Because DDNS allows the device to use an easier way to remember naming format rather than an IP address. The name of the domain is like the name of a person, and the IP address

is like his phone number. On the Internet we have IP numbers for each host (computer, server, router, and so on), and we replace these IP numbers to easily remember names, which are organized into the domain name. As to xDSL environment, most of the users will use dynamic IP addresses. If users want to set up a web or an FTP server, then the Dynamic Domain Name Server is necessary. For more DDNS configuration, please consult your dealer.

Your Internet Service Provider (ISP) provides you with at least one IP address which you use to connect to the Internet. The address you get may be static, meaning it never changes, or dynamic, meaning it's likely to change periodically. Just how often it changes, it depends on your ISP. A dynamic IP address complicates remote access since you may not know what your current WAN IP address is when you want to access your network over the Internet. The solution to the dynamic IP address problem comes in the form of a dynamic DNS service.

The Internet uses DNS servers to look up domain names and translates them into IP addresses. Domain names are just easy to remember aliases for IP addresses. A dynamic DNS service is unique because it provides a means of updating your IP address so that your listing will remain current when your IP address changes. There are several excellent DDNS services available on the Internet and best of all they're free to use. One such service you can use is www.DynDNS.org. You'll need to register with the service and set up the domain name of your choice to begin using it. Please refer to the home page of the service for detailed instructions or refer to Appendix E for more information.

DynDns.org, the procedures are:

- (1) Enable this service
- (2) Key-in the DynDNS server name, user name, and password.
- (3) Set up the IP Schedule update refreshing rate.
- (4) Click "**Apply**"
- (5) If setting up IP schedule update too frequently, the IP may be blocked. In general, it is recommended to schedule update every day (1440 minutes).

DDNS Setting

☒ Enabled
 ☐ Disabled

Provider:

dyndns.org

Hostname:

heaventea.dyndns-free

Username:

heaventea

Password:

•••••

Schedule Update:

30

 Minutes

State

Idle

Note:

1. Schedule Update: Depends on the input time of Schedule Update, it will update DDNS's web site automatically. The time range is from 5 to 5000 minutes.
*0: It will not update.
2. dyndns.org & 3322.org: Update once per day is recommended (1440 minutes per day). If updated too frequently, it will be blocked.

Apply

DDNS Status

- (1) Updating : Information update
- (2) Idle : Stop service
- (3) DDNS registration successful, can now log by <http://<username>.ddns.camddns.com> : Register successfully.
- (4) Update Failed, the name is already registered : The user name has already been used. Please change it.

- (5) Update Failed, please check your Internet connection : Network connection failed.
- (6) Update Failed, please check the account information you provide : The server, user name, and password may be wrong.

This model adds Planet easy DDNS that when enabled, this function will occur host name with PLANET DDNS and end six of MAC automatically. User does not need to go to web of www.planetddns.com to apply for the new account.

3.6.4 Mail & FTP & SAMBA

To send out the video via mail, FTP and Samba, please set up the configuration first.

Mail Setting:

Server Settings	
<u>Mail Setting</u>	
Login Method:	Account <input type="button" value="v"/>
Mail Server:	mail.planet.com.tw
Username:	admin
Password:	*****
Sender's Mail:	support@planet.com.tw
Receiver's Mail:	planet.test@gmail.com
Bcc Mail:	
Mail Port:	25 (Default 25)
<input type="checkbox"/> Secure Connect: <input checked="" type="radio"/> TLS <input type="radio"/> SSL	
<input type="button" value="Test"/>	
<u>FTP Setting</u>	
<u>Samba (Network storage)</u>	
<input type="button" value="Apply"/>	

Set up the server address and account information of your e-mail. Click "Apply" to save the setting, then use "Test" button to test the server connection. A message box will tell you "OK!" If it works, a test e-mail will be sent to receiver's mail address.

FTP Setting:

Server Settings	
<u>Mail Setting</u>	
<u>FTP Setting</u>	
FTP Server:	192.168.0.174
Username:	admin
Password:	*****
Port:	21
Path:	/VOLUME2/ADMIN/test
Mode:	PORT <input type="button" value="v"/>
Create the folder:	Yes <input type="button" value="v"/> (ex:Path/20100115/121032m.avi)
<input type="button" value="Test"/>	
<u>Samba (Network storage)</u>	
<input type="button" value="Apply"/>	

Set up the server address and account information of your FTP. Click "Apply" to save the setting, then use "Test" button to test the server connection. A message box will tell you "OK!" if it works, and a test file will be uploaded to FTP space.


In PORT mode, the FTP server builds the connection to the user's data port actively. However, from the user-side firewall's standpoint, the action of connecting from FTP server is often considered to be dangerous and should be blocked. In PASV mode, the problem is solved: The FTP server waits for the data transmission connection built by the user. Make sure that the server supports the mode you select.

Samba Setting:

Server Settings	
<u>Mail Setting</u>	
<u>FTP Setting</u>	
<u>Samba (Network storage)</u>	
Location:	<input type="text" value="192.168.0.124\share"/> (ex:\\Nas_ip\folder)
Workgroup:	<input type="text" value="workgroup"/>
Username:	<input type="text" value="admin"/>
Password:	<input type="password" value="•••••"/>
Create the folder:	Yes <input type="button" value="v"/> (ex:Path/20100115/121032m.avi)
<input type="button" value="Test"/> <input type="button" value="Apply"/>	

Select this option to send the media files via a network neighborhood when an event is triggered. Click "Apply" to save the setting, then use "Test" button to test the server connection. A message box will tell you "OK!" if it works, and a test document will be created in the location.

If the test fails, check the sharing setting of your location folder. The folder properties must be "shared" and the permissions must be "Full Control" as the picture.



Samba only supports one layer folder.

3.7 A/V Setting

3.7.1 Image Setting

For the security and privacy purposes, there are three areas that can be set up for privacy mask. Click Area button first and drag an area on the above image, and remember to save your setting. The masked area will not show on both the live viewing and recording.

Privacy Mask

Area 1 Area 2 Area 3 Save

Image Setting

Brightness: 0
Contrast: 0
Hue: 0
Saturation: 0
Sharpness: 0

AGC: 16x
Shutter Time: Outdoor
Sense-Up: 1/15
D-WDR: Off
Anti Fog: ☐ Enable
Lens Distortion Correction: Off
Video Orientation: ☐ Flip ☐ Mirror
Day & Night: Light Sensor Mode
Night to Day Lux: 7 lux (about) Day to Night Lux: 3 lux (about)
Current Lux: over 55 lux (about)
Red Gain: 0 Blue Gain: 0
Denoise: 3D: 3 2D: 1

Default

(1) Image adjust	Brightness, Contrast, Hue, Saturation, Sharpness can be adjusted here. The available values are: -4, -3, -2, -1, 0, 1, 2, 3, 4
(2) AGC	The sensitivity of the camera can adjust to the environmental lighting. Enable this function for getting brighter image on low light, but the level of noise may also increase. The available values are: 8x, 16x, 24x, 32x
(3) Shutter Time	Choose as the location of your camera or fixed shutter time. The shorter the shutter time is the less light the camera receives and the image becomes darker.
(4) Sense-Up	This function increases the sensitivity of camera to get brighter image at night. The smaller the value you select, the slower the shutter speed becomes so that the image will get brighter, and moving subjects might be blurred.
(5) D-WDR	Digital wide dynamic range. This function enables the camera to reduce the contrast in the view to avoid dark zones as a result of over and under exposure. If the Input resolution is 30fps, the default value is fixed on ENABLED. The available values are: OFF, 1, 2, 3, 4, 5, 6, 7, 8
(6) Anti Fog	Improve the image clarity on environments presenting high levels of fog or smoke.
(7) Lens Distortion Correction	Correct the image in the borders due to the lens angles. The available values are: OFF, 1, 2, 3, 4, 5, 6, 7, 8
(8) Video Orientation	Flip or mirror the image.
(9) Day & Night	The camera can detect the light level of the environment. If you choose "Light Sensor Mode", the image will be turned black and white at night in order to keep a clear image. To set light sensor mode, appoint a Lux standard of switching D/N.

	The current Lux value is provided for reference. Under "Times Mode" the switch time of Color / Black and white will be according to the given time. You can also control it by choosing "Color" or "B/W".
(10) Red / Blue gain	Set the values for Red / Blue gain. The available values are: -5, -4, -3, -2, -1, 0, 1, 2, 3, 4, 5
(11) Denoise	This function is able to filter the noise and blur from the image and show a clearer view. You can set the values for 2D and 3D filters.

3.7.2 Video Setting

Video Setting

Video System: NTSC

Video System: click the drop down list to select the system type "NTSC/PAL" and TV Output (analog signal).

Basic Mode :

Streaming 1 Setting

☒ Basic Mode ☐ Advanced Mode

Resolution: 1280x800

Profile: Main

Quality: Best

Video Frame Rate: 30 FPS

Video Format: H.264

RTSP Path: ex:rtsp://IP_Address/ Audio:G.711

Streaming 2 Setting

☒ Basic Mode ☐ Advanced Mode ☐ Close

Resolution: 1280x800

Profile: Baseline

Quality: Medium

Video Frame Rate: 15 FPS

Video Format: H.264

RTSP Path: v2 ex:rtsp://IP_Address/v2 Audio:G.711

Resolution	1280x800@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps (Max Video Frame Rate for both streaming combined is 30 FPS)
Profile	Choose between Main or Baseline.
Quality	There are 5 levels: Best/ High/ Standard/ Medium/ Low The higher the quality is, the bigger the file size is. Not good for internet transmission.

Video Frame Rate	The video refreshing rate per second. The max Value is affected by the input resolution you choose.
Video Format	H.264 and JPEG.
RTSP Path	Set the RTSP output connecting route.

Advanced Mode :

Streaming 1 Setting

☐ Basic Mode
 ☒ **Advanced Mode**

Resolution: 1280x800 ▼
Profile: Main ▼
Bitrate Control Mode: ☐ CBR ☒ **VBR**
Video Quantitative: 9 ▼
Video Bitrate: 8Mbps ▼
Video Frame Rate: 30 FPS ▼
GOP Size: 1 X FPS ▼ **GOP = 30**
Video Format: H.264 ▼
RTSP Path: ex:rtsp://IP_Address/ Audio:G.711

Streaming 2 Setting

☐ Basic Mode
 ☒ **Advanced Mode**
☐ Close

Resolution: 1280x800 ▼
Profile: Baseline ▼
Bitrate Control Mode: ☐ CBR ☒ **VBR**
Video Quantitative: 6 ▼
Video Bitrate: 512Kbps ▼
Video Frame Rate: 15 FPS ▼
GOP Size: 1 X FPS ▼ **GOP = 15**
Video Format: H.264 ▼
RTSP Path: v2 ex:rtsp://IP_Address/v2 Audio:G.711

Resolution	1280x800@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps (Max Video Frame Rate for both streaming combined is 30 FPS)
Profile	Chose between Main or Baseline.
Bitrate Control Mode	<p>There are CBR [Constant Bit Rate] and VBR [Variable Bit Rate] to use.</p> <p>CBR : 32Kbps~10Mbps (the higher the CBR is, the better the video quality is)</p> <p>VBR : 1(Low) ~10(High) – Compression rate, the higher the compression rate, the lower the picture quality is; vice versa. The balance between VBR and network bandwidth will affect</p>

	picture quality. Please carefully select the VBR rate to avoid picture breaking up or lagging.
Video Quantitative	The quality parameter of VBR. You can choose 1~10 compression rate. The higher the value is, the higher the image quality is.
Video Bitrate	The quality parameter of CBR. You can choose 32kbps ~ 8Mbps. The higher the value is, the higher the image quality is.
Video Frame Rate	The video refreshing rate per second. The max value is affected by the input resolution you choose.
GOP Size	It means "Group of Pictures". The higher the GOP is, the better the quality is.
Video Format	H.264 and JPEG
RTSP Path	RTSP output connecting route

3GPP Streaming mode:

3GPP Streaming Setting

☒ Open ☐ Close (Format=H.264)

Resolution: 320x240 ▼

Video Bitrate: 256Kbps ▼

Video Frame Rate: 15 FPS ▼

RTSP Path: v3 ex:rtsp://IP_Address/v3 Audio:AMR

The RTSP here is separated from the RTSP setting in the "IP SETTING". 3GPP Streaming can still work even you select "disabled" in the RTSP server option of IP Setting.

3GPP Resolution: 640 x 480 @15fps, 320 x 240 @ 15fps, 176 x 144 @ 15fps

Video compression: H.264, Audio compression: AMR.

3GPP Path: 3GPP output connecting route. If the IP address of your camera is 192.168.40.150, and you key in "3g" in the column, the 3GPP path will be rtsp://192.168.40.150/3g.

3.7.3 Audio Setting

The IP camera supports 2-way audio. User can send audio from IP camera's built-in microphone to remote PC; User can also send audio from remote PC to IP camera's external speaker.

(1) Audio from IP camera's built-in microphone to local PC: select "Enable" to start this function. The Audio compression format can be chosen from 3 options. You can also adjust the volume of 2-way audio.

Audio

IP Camera to PC

☒ Enabled ☐ Disabled

Audio Type: G.711 (64Kbps) ▼

Adjust Volume

Mic-In: 4 (Max) ▼

Line-Out: 4 (Max) ▼

Apply

(2) Audio from local PC to IP Camera: Check “**chatting**” on the browsing page.

 **PLANET**
Networking & Communication

HD IP Camera  



2014/APR/14 14:51:01 Size:1280x800 FPS: 18

default ▼ Streaming 1 ▼ Chatting: ☐ Online Visitor : 1 Relay Out: ☐ On ☒ OFF

3.8 Event List

3.8.1 Event Setting

Motion Detection



Area Setting: Area 1 Area 2 Area 3

Sensitivity: 5 5 5

☐ Area 1: ☐ E-mail ☐ FTP ☐ Out1 ☐ Save to SD card ☐ Samba

☐ Area 2: ☐ E-mail ☐ FTP ☐ Out1 ☐ Save to SD card ☐ Samba

☐ Area 3: ☐ E-mail ☐ FTP ☐ Out1 ☐ Save to SD card ☐ Samba

Subject:

Interval: 10 sec a period of time between every two motions detected.

☐ Based on the schedule

Record File

File Format: AVI File(with Record Time Setting)

Record Time Setting

Pre Alarm: 5 sec Post Alarm: 5 sec

Network Dis-connected

Dis-connected: ☐ Save to SD card

Network IP Check

IP Check: ☐ Enabled ☒ Disabled

IP Address:


Interval: 30 sec

Check failed: ☐ Connection failed four times. Reboot IP Camera.

☐ Save to SD card


Motion Detection

IP camera allows 3-area motion detection. When motion is triggered, it can send the video to some specific mail addresses, transmit the video to remote ftp server and SAMBA, and trigger the relay. To set up the motion area, click "Area Setting". Using mouse to drag and draw the area. The same operation for area 2 and 3. If you select "save to SD card", the video or sanpshot will be saved to Micro SD card. If you also tick E-mail/ FTP/ Samba of "Log" option, the motion detection log will be sent to E-mail/ FTP/ Samba simultaneously.

Interval	For example, if you select "10 sec" here, once the motion is detected and action is triggered, it cannot be triggered again within 10 seconds.
Based on the schedule	When the option box is ticked, only during the selected schedule time the motion detection is enabled. That is, for example, the 11th hour of Monday has not been colored in the schedule table, then no action will be triggered even the camera detects motion during 11:00~12:00 on Monday.
Record File Setting	IP camera allows 3 different types of recording file to change its record size. When motion/alarm is triggered, there are 3 different types of recording modes: (1) AVI File (With Record File Setting) (2) Multi-JPEG (With Record File Setting), only with JPEG compression format. (3) Single JPEG (Single File with Interval Setting)
Record Time Setting	Pre Alarm and Post Alarm setups for video start and end time when motion detects I/O, or other devices got triggered. <div>  <p>Note Pre/Post Alarm record time is based on record time setting and IP cam built-in Ram memory. Limited by IP cam built-in Ram Memory, when information is too much or video quality set too high, it will cause recording frame to drop or decrease on post alarm recording time.</p> </div>
Network Dis-connected	To avoid video loss, the camera will start to save the video to local SD card when it detects no network connection. The video recording will continuously be saved into SD card and divided into every 10 minutes a file until the network is reconnected successfully. The oldest file will be deleted if the capacity of SD card is full.
Network IP check	Key in the target IP address and interval. The camera checks once in a while according to the setting interval time if it can link to the target IP address. If connection fails, the camera starts to save the video to SD card

3.8.2 Schedule

Schedule																								
All	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
Mon.																								
Tue.																								
Wed.																								
Thu.																								
Fri.																								
Sat.																								
Sun.																								

 **With schedule setup.**

Snapshot	
<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled	
Snapshot:	<input type="checkbox"/> E-mail <input type="checkbox"/> FTP <input type="checkbox"/> Save to SD card <input type="checkbox"/> Samba
Interval:	<input type="text" value="10"/> Second(s) [1..50000]
File Name:	<input type="text" value="Snapshot"/>

Schedule	After complete the schedule setup, the camera data will be recorded according to the schedule setup.
Snapshot	After enable the snapshot function, user can select the storage position of snapshot file, the interval time of snapshot and the reserved file name of snapshot.
Interval	The interval between two snapshots.

3.8.3 I/O Setting

The ICA-3110 supports 1 input/1 output. When input is triggered, it can send the video to some specific mail addresses, transmit the video to remote ftp server, and trigger the relay and SAMBA.

I/O Setting

Input Setting

Input 1 Sensor: N.O

Input 1 Action: ☐ E-mail ☐ FTP ☐ Out1 ☐ Save to SD card ☐ Samba

Subject: GPIO In Detected!

Interval: 10 sec


☐ Based on the schedule

Output Setting

Mode Setting: ☒ OnOff Switch ☐ Time Switch

Interval: 10 sec

Alarm Input Setting	The GPIO I/O port input activates related action when I/O input is triggered.
Interval	For example, if you select "10 sec" here, once the motion is detected and action is triggered, it cannot be triggered again within 10 seconds.
Based on the schedule	When the option box is ticked, only during the selected scheduled time the I/O is enabled. That is, for example, the 11th hour of Monday has not been colored in the scheduled table, then no action will be triggered even the camera detects input signal during 11:00~12:00 on Monday.
GPIO Output Setting	The GPIO I/O port output activates On/Off Switch, Slide Switch or Pan/Tilt Module for use with relay box.
On Off Switch	The camera triggers the external devise and lasts for 10 seconds. You can turn off the alarm manually by clicking "off" at the right bottom of the live video page.
Time Switch	The camera triggers the external device and lasts for certain of time according to the interval setting, and the user is not allowed to break off the alarm manually.



Please connect to propriety relay box to reduce the risk of electric shock and damage.

3.8.4 Log List

Sort by System Logs, Motion Detection Logs and I/O Logs. In addition, System Logs and I/O Logs won't lose data due to power failure.

Log List	
System Logs	Logs
Motion Detection Logs	Logs
I/O Logs	Logs
All Logs	Logs

3.8.5 SD card

Playback

Please Insert Micro SD card before using it. Make sure to push Micro SD card into the slot completely.
Click the date listed on this page and it shows the list of the video. The video format is AVI.
Click the video to start Microsoft Media Player to play it. To delete the video, check it, and then click "Del".

Playback			
20121019	20121023	20121024	
SD Card: << 856M / 969M >>			

2012/10/23			Del
Time	Video	Event Type	<input type="checkbox"/>
11:55:48	115548m.avi	Motion Detection	<input type="checkbox"/>
12:22:16	122216m.avi	Motion Detection	<input type="checkbox"/>
12:23:01	122301m.avi	Motion Detection	<input type="checkbox"/>
12:24:06	122406m.avi	Motion Detection	<input type="checkbox"/>
12:25:04	122504m.avi	Motion Detection	<input type="checkbox"/>
Files link daily.			

SD Management

Choose "The 1st day" means the recoding file will be kept for one day. For example, it is five o'clock now. Choose "The 1st day". The files will be kept from five o'clock yesterday to five o'clock today.

The oldest file will be deleted if the Micro SD card is full.

Playback

No SD card

SD Management

Auto Deletion: Off (Keep 1/ 2/ 3/ 4...days)

Off

The 1st day

The 2nd day

The 3rd day

The 4th day

The 5th day

The 6th day

The 7th day

The 8th day

The 9th day

The 10th day


The 15th day

The 20th day

The 25th day

The 30th day

Apply

 **Note** The use of the SD card will affect the operation of the IP Camera slightly, such as affecting the frame rate of the video.


Copy to PC

You can insert the Micro SD card into PC and read the files directly, or use FlashGet instead to download the files from IP camera. (In this way you do not need to pull out Micro SD card from the camera.)


To use FlashGet for downloading the image and video data from the Micro SD card, please follow the steps:




Open FlashGet, select "File" → "Import" → "Import list", and find the link list file you just saved. The file name may be called "SD_list".



FlashGet will show you the link list, and you can tick the files you want to copy to your PC. Give the directory path in the new download window, and remember to enable "Login to Server":
Key in the IP camera user name and password.




Click **OK** to start download



FlashGet is a free software that can be downloaded from FlashGet official website. The example above is based on FlashGet ver.1.9.6.1073


Appendix A: I/O Configuration

1. I/O Connection



A. Please connect the G & DO pin to the external relay (buzzer) device.


When no event happens, DO output is 5V (DO and GND are disconnected). When the camera detects event happening and triggers external alarm, DO output is 0V (DO and GND are connected).



B. Please connect the G & DI pin to the external trigger device.

If you select "N.O" in "Input sensor setting", when external device or circuit makes DI and GND pin connected, the camera input alarm is triggered, and then camera will execute the action user has set, for example, send snapshot to E-mail address.

If you select "N.C" in "Input sensor setting", when external device or circuit makes DI and GND pin disconnected, the camera input alarm is triggered, and then camera will execute the action user has set, for example, send snapshot to E-mail address.



C. I/O PIN definition

- GND (Ground): Initial state is LOW
- DO (Digital Output): DC 5V
- DI (Digital Input): Max. 50mA, DC 5V

2. I/O Setup

A. Click I/O Setting from the system setup page via IE, and check "Out1" to enable I/O signal.

I/O Setting

Input Setting

Input 1 Sensor:

Input 1 Action: ☒ E-mail ☒ FTP ☐ Out1 ☐ Save to SD card ☒ Samba

Subject:

Interval:

☐ Based on the schedule

Output Setting

Mode Setting: ☒ OnOff Switch ☐ Time Switch


Interval:

B. Output Test

After the external input and output hardware is installed, you can use the "Relay Out" bottom on the live video page to test if DO / Relay Out works.


1) OnOff Switch mode:

Click "ON" and the camera will trigger the external output device. For example, your alarm buzzer will continuously ring. You can manually break off the output signal by clicking "OFF".



2) Time Switch mode:

Click "Pulse" and the camera will trigger the external output device for several seconds. The duration length is according to the "interval" setting in Output Setting.




Appendix B: PING IP Address

The PING (stands for Packet Internet Groper) command is used to detect whether a specific IP address is accessible by sending a packet to the specific address and waiting for a reply. It's also a very useful tool to confirm whether or not Internet camera installed or if the IP address conflicts with any other device over the network.

If you want to make sure the IP address of Internet camera, utilize the PING command as follows:

- Start a DOS window.
- Type ping x.x.x.x, where x.x.x.x is the IP address of the Internet camera.

The replies, as illustrated below, will provide an explanation to the problem.



```
C:\> Command Prompt
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

D:\Documents and Settings\Administrator>PING 192.168.0.20

Pinging 192.168.0.20 with 32 bytes of data:

Reply from 192.168.0.20: bytes=32 time=1ms TTL=64
Reply from 192.168.0.20: bytes=32 time<1ms TTL=64
Reply from 192.168.0.20: bytes=32 time<1ms TTL=64
Reply from 192.168.0.20: bytes=32 time<1ms TTL=64


Ping statistics for 192.168.0.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

D:\Documents and Settings\Administrator>_
```

If you want to detect any other device that conflicts with the IP address of Internet camera, you also can utilize the PING command but you must disconnect the Internet camera from the network first.

Appendix C: 3GPP Access

To use the 3GPP function, in addition to the previous section, you might need more information or configuration to make this function work.



To use the 3GPP function, it is strongly recommended to install the Networked Device with a public and fixed IP address without any firewall protection.

RTSP Port:

Port 554 is the default for RTSP service. However, sometimes, some service providers change this port number for some reasons. If so, user needs to change this port accordingly.

Dialing procedure:

1. Choose a verified player (PacketVideo or Realplayer)
2. Use the following default URL to access:

rtsp://IP-Address/3g

Where *host* is the host name or IP address of the camera.

Compatible 3G mobile phone:

Please contact your dealer to get the approved list of compatible 3G phones.



Besides IP camera and 3G mobile phone, you will also need to make sure the ISP and company have provided the 3GPP service to you.

Appendix D: PLANET DDNS Application

Configuring PLANET DDNS steps:

Step 1 Enable DDNS option through accessing web page of the ICA-3110.

DDNS Setting

☒ Enabled ☐ Disabled

Step 2 Select on DDNS server provided, and register an account if you do not use yet.



The image shows the PLANET DDNS login interface. At the top is the PLANET DDNS logo. Below it is a 'Sign in' section with two input fields: 'ID / Email' and a password field (masked with dots). A 'Sign in' button is to the right of the password field. Below the login fields are links for 'Forgotten Password' and 'Create A New Account'.

Step 3 After login, please add your device.



The image shows the 'My Devices' page in the PLANET DDNS application. The top navigation bar has 'Home', 'My Devices' (selected), and 'Profile'. The main content area is titled 'New Device' and contains two input fields: 'Registered Domain' (with 'frankt' entered) and 'Name of Your Device' (with 'ICA-HM101' entered). The domain field has '.planetddns.com' as a placeholder. At the bottom are 'Cancel' and 'Submit' buttons.

Step 4 Set your camera IP to public.

IP Setting

IP Assignment

☐ DHCP

☒ Static

IP Address: 210.66.155.81

Subnet Mask: 255.255.255.224

Gateway: 210.66.155.94

DNS 0: 168.95.1.1

DNS 1: 8.8.8.8

Step 5 Fill out the blank of the DDNS setting. (The user name and password here are the same as your registered user name and password on the planetddns website.)

DDNS Setting

☒ Enabled ☐ Disabled

Provider: PLANET DDNS

Hostname: frankt.planetddns.co

Username: frankt

Password:

Schedule Update: 60 Minutes

Step 6 After the setting is done, for example, we can enter <http://frankt.planetddns.com/> to access the camera, and you can see your device photo and “Ping Status” is green on the planetddns website.

 PLANET DDNS

PLANET Website [FAQ](#)

[Home](#) [My Devices](#) [Profile](#)

Welcome, frank ([Sign out](#))

[Add Device](#) 

IP-Camera

No.	Image	Your Device	Registered Domain	Name of Your Device	Last Connection IP	Ping Status	Modify	Delete
1		ICA-HM101	frankt	ICA-HM101	210.66.155.77			

Appendix E: Configuring Port Forwarding Manually

The device can be used with a router. If the device wants to be accessed from the WAN, its IP address needs to be set up as a fixed IP address. The port forwarding or Virtual Server function of router also needs to be set up. This device supports UPnP traversal function. Therefore, user could use this feature to configure port forwarding of NAT router first. However, if user needs to configure port forwarding manually, please follow the steps below:

Manually installing the device with a router on your network is an easy 3–step procedure as following:

1. Assign a local/fixed IP address to your device
2. Access the Router with Your Web browser
3. Open/Configure Virtual Server Ports of Your Router

1. Assign a local/fixed IP address to your device

The device must be assigned a local and fixed IP Address that allows it to be recognized by the router. Manually set up the device with a fixed IP address, for example, 192.168.0.100.

2. Access the Router with Your Web browser

The following steps generally apply to any router that you have on your network. PLANET WNRT-620 is used as an example to clarify the configuration process. Configure the initial settings of the router by following the steps outlined in the router's **Quick Installation Guide**. If you have cable or DSL service, you will most likely have a dynamically assigned WAN IP Address. 'Dynamic' means that your router's WAN IP address can change from time to time depending on your ISP. A dynamic WAN IP Address identifies your router on the public network and allows it to access the Internet. To find out what your router's WAN IP Address is, go to the **Status** screen on your router and locate the WAN information for your router. As shown on the following page the WAN IP Address will be listed. This will be the address that you will need to type in your web browser to view your camera over the Internet. Be sure to uncheck the **Reset IP address at next boot** button at the top of the screen after modifying the IP address. Failure to do so will reset the IP address when you restart your computer.

Home | General Setup | Status | Tool

Internet Broadband Router

Status

- Internet Connection
- Device Status
- System Log
- Security Log
- Active DHCP Client
- Statistics

Current Time
1/1/2000 2:01:15

Internet Connection

View the current internet connection status and related information.

Attain IP Protocol :	Dynamic IP disconnect
IP Address :	
Subnet Mask :	
Default Gateway :	0.0.0.0
MAC Address :	00:11:22:33:44:56
Primary DNS :	
Secondary DNS :	

Your WAN IP Address will be listed here.

3. Open/set Virtual Server Ports to enable remote image viewing

The firewall security features built into the router and most routers prevent users from accessing the video from the device over the Internet. The router connects to the Internet over a series of numbered ports. The ports normally used by the device are blocked from access over the Internet. Therefore, these ports need to be made accessible over the Internet. This is accomplished using the **Virtual Server** function on the router. The Virtual Server ports used by the camera must be opened through the router for remote access to your camera.


Follow these steps to configure your router's Virtual Server settings

- Click **Enabled**.
- Enter a unique name for each entry.
- Select **Both** under **Protocol Type (TCP and UDP)**
- Enter your camera's local IP Address (e.g., **192.168.0.100**, for example) in the **Private IP** field.
- If you are using the default camera port settings, enter **80** into the **Public** and **Private Port** section, click **Add**.

A check mark appearing before the entry name will indicate that the ports are enabled.

Note

Some ISPs block access to port 80. Be sure to check with your ISP so that you can open the appropriate ports accordingly. If your ISP does not pass traffic on port 80, you will need to change the port the camera uses from 80 to something else, such as 8080. Not all routers are the same, so refer to your user manual for specific instructions on how to open ports.


Home | General Setup | Status | Tool

Internet Broadband Router

- System
- WAN
- LAN
- Wireless
- QoS
- NAT
 - Port Forwarding
 - Virtual Server
 - Special applications
 - UPnP Setting
 - ALG Settings
- Firewall

Virtual Server ?

You can configure the Broadband router as a Virtual Server so that remote users accessing services such as the Web or FTP at your local site via Public IP Addresses can be automatically redirected to local servers configured with Private IP Addresses. In other words, depending on the requested service (TCP/UDP) port number, the Broadband router redirects the external service request to the appropriate internal server (located at one of your LAN's Private IP Address).

☒ Enable Virtual Server

Private IP	Private Port	Type	Public Port	WAN Port	Comment
<input type="text"/>	<input type="text"/>	Both	<input type="text"/>	WAN1	<input type="text"/>

Current Virtual Server Table:

Private IP	Private Port	Type	Public Port	WAN Port	Comment	Select
192.168.0.100	80	TCP+UDP	80	WAN1	ICA-HM230	<input type="checkbox"/>

Enter valid ports in the **Virtual Server** section of your router. Please make sure to check the box on this line to enable settings. Then the device can be accessed from WAN by the router's WAN IP Address.

By now, you have finished your entire PC configuration for this device.

Appendix F: Troubleshooting & Frequently Asked Questions

Features	
The video and audio codec is adopted in the device.	<p>The device utilizes H.264, MPEG-4 and M-JPEG triple compression to provide high quality images. Where H.264 and MPEG-4 are standards for video compression and M-JPEG is a standard for image compression.</p> <p>The audio codec is defined as AMR for 3GPP and G.711 for RTSP streaming.</p>
The maximum number of user that accesses the device simultaneously.	The maximum number of users is limited to 10. However, it also depends on the total bandwidth accessed to this device from clients.
Install this device	
The network cabling is required for the device.	The device uses Category 5 UTP cable allowing 10 and/or 100 Base-T networking.
The device will be installed and work if a firewall exists on the network.	If a firewall exists on the network, port 80 is open for ordinary data communication. The HTTP port and RTSP port need to be opened on the firewall or NAT router.
The username and password for the first time or after factory default reset	<p>Username = admin and Password = admin.</p> <p>Note that it's all case sensitivity.</p>
Forgot the username and password	<p>Follow the steps below:</p> <ol style="list-style-type: none"> (1) Remove power, and press and hold the button in the back of IP camera. (2) Power on the camera. Don't release the button during the system booting. (3) It will take around 30 seconds to boot the camera. (4) Release the button when camera finishes proceed. (5) Re-login the camera using the default IP (http://192.168.0.20), and username (admin), password (admin).
Forgot the IP address of the device.	Check IP address of device by using the PLANET IP Installer program or by UPnP discovery or set the device to default by Reset button.
PLANET IP Installer program cannot find the device.	<ul style="list-style-type: none"> ● Re-power the device if cannot find the unit within 1 minute. ● Do not connect device over a router. PLANET IP Installer program cannot detect device over a router. ● If IP address is not assigned to the PC that runs PLANET IP Installer program, then PLANET IP Installer program cannot find device. Make sure that IP address is assigned to the PC properly. ● Antivirus software on the PC might interfere with the setup program. Disable the firewall of the antivirus software during

	<p>setting up this device.</p> <ul style="list-style-type: none"> • Check the firewall setting of your PC or Notebook.
Internet Explorer does not seem to work well with the device	Make sure that your Internet Explorer is version 6.0 or later. If you are experiencing problems, try upgrading to the latest version of Microsoft's Internet Explorer from the Microsoft webpage.
PLANET IP Installer program fails to save the network parameters.	Network may have trouble. Confirm the parameters and connections of the device.
UPnP NAT Traversal	
Cannot work with NAT router	Maybe NAT router does not support UPnP function. Please check user's manual of router and turn on UPnP function.
Some IP cameras are working but others failed	Maybe too many IP cameras have been installed on the LAN, and then NAT router is out of resource to support more cameras. You could turn off and on NAT router to clear out of date information inside router.
Access this device	
Cannot access the login page and other web pages of the Network Camera from Internet Explorer	<ul style="list-style-type: none"> • Maybe the IP Address of the Network Camera is already being used by another device or computer. To confirm this possible problem, disconnect the Network Camera from the network first, and then run the PING utility to check it out. • Maybe it's the network cable. Try correcting your network cable and configuration. Test the network interface by connecting a local computer to the Network Camera via a crossover cable. • Make sure the Internet connection and setting is ok. • Make sure the IP address of Internet Explorer you entered is correct. If the Network Camera has had a dynamic address, it may have changed since you last checked it. • Network congestion may prevent the web page from appearing quickly. Wait for a while. <p>The IP address and Subnet Mask of the PC and Network Camera must be in the same class of the private IP address on the LAN.</p> <ul style="list-style-type: none"> • Make sure the http port used by the Network Camera, default=80, is forward to the Network Camera's private IP address. • The port number assigned in your Network Camera might not be available via Internet. Check your ISP for available port. • The proxy server may prevent you from connecting directly to the Network Camera. You are advised not to use the proxy server. • Confirm that Default Gateway address is correct. • The router needs Port Forwarding feature. Refer to your router's manual for details. • Packet Filtering of the router may prohibit access from an external network. Refer to your router's manual for details. • Access the Network Camera from the Internet with the global IP address of the router and port number of Network Camera.

	<ul style="list-style-type: none"> Some routers reject the global IP address to access the Network Camera on the same LAN. Access with the private IP address and correct port number of Network Camera. When you use DDNS, you need to set Default Gateway and DNS server address. If it's not working after following the above procedure, reset Network Camera to default setting and install it again.
Image or video does not appear on the main page.	<ul style="list-style-type: none"> The first time the PC connects to Network Camera, a pop-up Security Warning window will appear to download ActiveX Controls. When using Windows XP, or Vista, log on with an appropriate account that is authorized to install applications. Network congestion may prevent the Image screen from appearing quickly. You may choose lower resolution to reduce the required bandwidth.
How to check whether the device's ActiveX is installed on your computer	Go to C:\Windows\Downloaded Program Files and check to see if there is an entry for the file " Web Watch2 Control ". The status column should show "Installed". If the file is not listed, make sure your Security Settings in Internet Explorer are configured properly and then try reloading the device's home page. Most likely, the ActiveX control did not download and install correctly. Check your Internet Explorer security settings and then close and restart Internet Explorer. Try to browse and log in again.
Internet Explorer displays the following message: "Your current security settings prohibit downloading ActiveX controls".	Setup the IE security settings or configure the individual settings to allow downloading and scripting of ActiveX controls.
The device works locally but not externally.	<ul style="list-style-type: none"> Might be caused from the firewall protection. Check the Internet firewall with your system or network administrator. The firewall may need to have some settings changed in order for the device to be accessible outside your LAN. Make sure that the device isn't conflicting with any other web server running on your LAN. Check the configuration of the router settings to allow the device to be accessed outside your local LAN. Check the bandwidth of Internet connection. If the Internet bandwidth is lower than target bit rate, the video streaming will not work correctly.
The unreadable characters are displayed.	Use the operating system of the selected language. Set the Encoding or the Character Set of the selected language on the Internet Explorer.
Frame rate is slower than the setting.	<ul style="list-style-type: none"> The traffic of the network and the object of the image affect the frame rate. The network congestion causes frame rate slower than the setting. Check the bandwidth of Internet connection. If the Internet bandwidth is lower than target bit rate, the video streaming will not work correctly.

	<ul style="list-style-type: none"> • Ethernet switching hub can smooth the frame rate.
Image Transfer on e-mail or FTP does not work.	<ul style="list-style-type: none"> • Default Gateway and DNS server address should be set up correctly. • If FTP does not work properly, ask your ISP or network administrator about the transferring mode of FTP server.
Video quality of the device	
The focus on the Camera is bad.	The lens is dirty or dust is attached. Fingerprints, dust, stain, etc. on the lens can degrade the image quality.
The color of the image is poor or strange.	<ul style="list-style-type: none"> • Adjust White Balance. • To ensure the images you are viewing are the best they can be, set the Display property setting (color quality) to 16bit at least and 24 bit or higher if possible within your computer. • The configuration on the device image display is incorrect. You need to adjust the image related parameters such as brightness, contrast, hue and sharpness properly.
Image flickers.	<ul style="list-style-type: none"> • If the object is dark, the image will flicker. Make the condition around the Camera brighter.

Appendix G: Micro SD Card Compatibility

The following is the Micro SD Card recommended:

Transcend	SDHC	class4	16GB
	SDHC	class4	32GB
	SD	class4	16GB
	SD	class4	32GB
	SDHC	class6	4GB
	SDHC	class6	8GB
	SDHC	class6	16GB
	SD	class6	4GB
	SD	class6	8GB
	SD	class6	16GB
	SDHC	class10	4GB
	SDHC	class10	8GB
	SDHC	class10	
SanDisk	SDHC	class4	4GB
	SDHC	class4	8GB
	SDHC	class4	16GB
	SDHC	class4	32GB