

## IEEE 802.11b SIP Wi-Fi Phone



Based on years of VoIP manufacturing experiences, PLANET Technology VoIP total solutions are known for advanced implementation of standards based telephony with mass deployment capability.

Cost-effective, easy-to-install and simple-to-use, the portable VoIP solution

- PLANET 802.11b Wi-Fi phone - VIP-190, a mobile phone that unleash your voice communications free from wire. Combining PLANET wireless MESH solution, the VIP-190 is ideal for the daily office communications, ITSP (Internet Telephony Service Providers) and enterprises users to offer toll-quality voice communication services via the existing corporation network or Internet access

### KEY FEATURE

#### Product features


- Feature-rich mobile VoIP service in your daily life
- Cost effective, field proven compatibility, and stability
- Web-based and LCD menu machine configuration
- Remote HTTP administrator authentication
- Layer 3 ToS / DiffServ support for various VoIP applications
- tandby time 24 hour; talking time 4 hours

#### VoIP Features

- SIP 2.0 (RFC 3261), SDP (RFC 2327) compliant
- SIP Outbound Proxy / SIP STUN Server support
- Peer-to-Peer / SIP proxy calls
- Voice codec support: G711, G.729a
- Voice processing: Voice Active Detection (VAD), DTMF detection/ generation, G.168 echo cancellation, Comfort noise generation (CNG)
- Built-in phone book

**SPECIFICATION**
**Product** 802.11b Wi-Fi Phone

<b>Model</b>	VIP-190
<b>Hardware</b>	
<b>WLAN</b>	IEEE 802.11b
<b>Security</b>	64/128 Bit WEP encryption
<b>WLAN Feature</b>	Site survey and wireless profile
<b>Protocols and Standard</b>	
<b>Standard</b>	SIP 2.0 (RFC3261), SDP (RFC2327), SIP Outbound proxy, STUN (RFC 3489)
<b>Voice codec</b>	G.711, G.729a
<b>Voice Standard</b>	Voice activity detection (VAD) Comfort noise generation (CNG) G.168 echo cancellation (EC) Silence suppression
<b>Protocols</b>	SIP 2.0 (RFC3261), TCP/IP, UDP/RTP/RTCP, HTTP, ICMP, ARP, DNS, DHCP, PPPoE
<b>Network and Configuration</b>	
<b>Access Mode</b>	Static IP, DHCP, PPPoE
<b>Management</b>	Web, LCD menu
<b>Dimension (W x D x H)</b>	126 x 46 x 20 mm
<b>Operating Environment</b>	0~40 Degree C, 10~95% humidity
<b>Power Requirement</b>	3.7V, 1350mA (battery); one mini-USB connector for charger
<b>EMC/EMI</b>	CE, FCC Class B

**APPLICATIONS**

**ORDERING INFORMATION**

<b>VIP-190</b>	IEEE 802.11b SIP Wi-Fi Phone (802.11b WLAN)
<b>VIP-190 SPK</b>	Hand-free speaker phone / charge for VIP-190