



Smart Fast Ethernet Media Converter Comparison Table

Date: June 5, 2007

| Model name | WFT-8 series | FST-8 series |
|-------------------------|---|--|
| |  |  |
| Dimension (W x D x H) | 88 x 120 x 25 mm | 81 x 94 x 26mm |
| Weight | 0.4kg | 0.22kg |
| Power input | DC 7.5V 1A | DC 5V 2A |
| Power consumption | 7.2 Watts / 24.5 BTU (maximum) | 6.2 Watts / 21 BTU (maximum) |
| Ethernet Interfaces | One 10/100Base-TX port , one 100Base-FX port | One 10/100Base-TX port , one 100Base-FX port |
| LED indicator | System: PWR TP: FAIL, LINK/ACT, FDX, 100 FX: FAIL, LINK/ACT, FDX | System: PWR TP: LNK/ACT, FDX/COL, 100 FX: LNK/ACT, FDX/COL |
| DIP Switch | Fiber and UTP (FDX/HDX), UTP (Auto-negotiation/Manual), Speed (10M/100M), LLR Enable/Disable, LLCF (Enable/Disable) | Fiber (HDX/FDX), UTP (Auto-negotiation / Manual), speed (10/100Mbps), duplex mode (Half / Full duplex mode), LLR (Disable / Enable), LLCF (Disable / Enable) |
| Media Converter Chassis | WMC-1600R / WMC-1600R48 | MC-1600MR / MC-1600MR48 |
| Standards | IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100 Base-TX / FX Fast Ethernet | IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100 Base-TX / FX Fast Ethernet |
| Emissions | FCC Class B, CE Class B | FCC Class B, CE Class B |