



Model name	FSD-503v2	FSD-503v3
Level	Unmanaged	Unmanaged
Outlook		
Hardware specification		
10/100Base-TX ports	5	5
LED Display	One for Power, One for Link / Act per port	One for Power, One for Link / Act per port
Dimension (Wx D x H)	160 x 80 x 28 mm	160 x 80 x 28 mm
Weight	325g	325g
Power Requirement	DC 12V, 500mA	DC 12V, 500mA
Power Consumption / Dissipation	2.6 Watts / 8.8 BTU	2.6 Watts / 8.8 BTU
Power ON / OFF button	None	Yes
Switch Specification		
Switch Processing Scheme	Store-and-Forward	Store-and-Forward
MAC Address Table	2K	2K
Packet Buffer Memory	384K bits	384K bits
Flow Control	Back pressure for half duplex, IEEE 802.3x Pause Frame for full duplex	Back pressure for half duplex, IEEE 802.3x Pause Frame for full duplex
Switch Fabric	1Gbps	1Gbps
Throughput (Packet Per Second)	0.74Mpps	0.74Mpps
Standard Conformance		
Ethernet Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3x Full-duplex Flow Control	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3x Full-duplex Flow Control
Temperature	Operating: 0~50 Degree C, Storage: -10~70 Degree C	Operating: 0~50 Degree C, Storage: -10~70 Degree C
Humidity	Operating: 5~90%, Storage: 5~90% (Non-Condensing)	Operating: 5~90%, Storage: 5~90% (Non-Condensing)
Regulation Compliance	FCC Part 15 Class A, CE	FCC Part 15 Class A, CE
Remark		