



IP Intercoms Comparison Table -- Internal		
	Date: 22/9/2016	Made by Ines
Model	HDP-5260PT	HDP-1100PT
		
Hardware		
Indoor/Outdoor	Outdoor	Indoor
Protection Level	IP65 and IK10	n/a
Operating Temperature	-40~70 degrees C	-10~45 degrees C
Anti-tamper	Yes	n/a
Numeric Keypad	12 keys + 1 Speed Dial	1 Speed Dial
Access Control	RFID, Password and DTMF Code	DTMF Code
Ethernet	10/100/1000Mbps	10/100Mbps
PoE	802.3af, Class 3	802.3af, Class 3
Acoustic Echo Canceller	Yes	Yes
Microphone	Full-duplex speaker and Noise Reduction with dual mics	Full-duplex speaker
Video & Audio		
Camera	1280 x 760, CMOS sensor	1280 x 720, CMOS sensor
Video Frame Rate	30fps	20fps
Monitoring Range	5 meters	3 meters
LED	IR LED x 3, effective up to 2 meters	White LED x 6, effective up to 0.6 meter
Video Codec	H.264/H.263	H.264
Voice Codec	G.711a/u, G.722, G.723.1, G.726, G.729AB, iLBC and AMR	G.711a/u, AAC
Lines	2 SIP lines	1 SIP line
Networking & Protocols		
QoS	Yes	-
IEEE 802.1x	Yes	-
VPN	L2TP, PPTP, IPSec	-
VLAN	802.1p/q	-
HTTPS & TR069	Yes	-
Deployment & Maintenance		
Auto-Provisioning	FTP, TFTP, HTTP, HTTPS, DHCP, TR069, and SIP PNP	-
Entry Log Export	Yes	-
Access Table Export/Import	Yes	-
Syslog (including Open Door Log)	Yes	-
Installation	Wall-mount type	Wall-mount type