

Multi-Homing Security Gateway



The innovation of the Internet has created a tremendous worldwide venue for e-business and information sharing, but it also creates network security problems, so the security request will be the primary concerned for the enterprise. Planet's Content Security Gateway CS-1000, a special designed of security gateway for small business, adopts Heuristics Analysis to filter spam and virus mail, auto-training system can raise identify rate of spam, and built-in Clam virus scan engine can detect viruses, worms and other threats from email transfer.

Meanwhile, Instant Messaging (IM) and peer-to-peer (P2P) are the fastest growing communications medium of all time, the spread of IM and P2P has created a network security threats and consumed amount of bandwidth. CS-1000 also can prevent employees using varied IM and P2P like MSN, Yahoo Messenger, ICQ, QQ and Skype.

CS-1000 not only can filter spam and virus mail, but also is a high performance VPN firewall. The firewall function can defense hacker and blaster attack from Internet. Furthermore, QoS and User Authentication features are available now, it makes CS-1000 to a completely security gateway and can fulfill varied of customer's need.

KEY FEATURE

Anti-Spam Filtering

- Multiple defense layers (Head Analysis, Text Analysis, Blacklist & Whitelist, Bayesian Filtering), and Heuristics Analysis to block over 95% spam mail. Customizable notification options and spam mail report are provided for administrator. Varied actions toward spam mail include: Delete, Deliver, and Forward. Built-in auto-training system to rise identify rate of spam mail substantially.

Anti-Virus Protection

- Built-in Clam virus scan engine can detect viruses, worms, and other threats from email transfer. Scan mission-critical content protocols-SMTP, POP in real time as traffic enters the network to provide maximum protection. Customizable notification options and virus mail report are provided for administrator. Varied actions toward spam mail include: Delete, Deliver, and Forward.

WAN Backup

- The CS-1000 can monitor each WAN link status and automatically activate backup links when a failure is detected. The detection is based on the configurable target Internet addresses.

Outbound Load Balancing

- The network sessions are assigned based on the user configurable load balancing mode, including "Auto", "Round-Robin", "By Traffic", "By Session" and "By Packet". User can also configure which IP or TCP/UDP type of traffic use which WAN port to connect.

VPN Connectivity

- The security gateway support PPTP server/client and IPSec VPN. With DES, 3DES and AES encryption and SHA-1/MD5 authentication, the network traffic over public Internet is secured.

Content Filtering

- The security gateway can block network connection based on URLs, Scripts (The Pop-up, Java Applet, cookies and Active X), P2P (eDonkey, Bit Torrent and WinMX), Instant Messaging (MSN, Yahoo Messenger, ICQ, QQ and Skype) and Download. If there are new updated version of P2P or IM software in client side, CS-1000 will detect the difference and update the Content Filtering pattern to renew the filtering mechanism.

IDP

- CS-1000 provides three kinds of the Signature to complete the intrusion detection system, user can select to configure "Anomaly", "Pre-defined" and "Custom" according to the current environment's request.

QoS

- Network packets can be classified based on IP address, IP subnet and TCP/UDP port number and give guarantee and maximum bandwidth with three levels of priority.

Authentication

- Web-based authentication allows users to be authenticated by web browser. User database can be configured on the devices or through external RADIUS server.

Multiple NAT


- Multiple NAT allows local port to set multiple subnet works and connect to the Internet through different WAN IP addresses.

SPECIFICATION
Product Multi-Homing Security Gateway

Model	CS-1000	
Hardware		
Ethernet	LAN	1 x 10/100Mbps RJ-45
	WAN	2 x 10/100Mbps RJ-45
	DMZ	1 x 10/100Mbps RJ-45
Power	100~250 VAC	
Operating Environment	Temperature: 0 ~ 60°C	
	Relative Humidity: 5% ~ 95%	
Dimension (W x D x H)	440 x 237 x 43 mm	
Regulatory	FCC, CE Mark	
Software		
Management	Web	
Network Connection	Transparent, NAT, Multi-NAT	
Outbound Load Balancing	Policy-based routing	
	Load-balancing by Round-Robin, traffic, session and packet	
Routing Mode	Static Route, RIPv2	
Firewall	Policy-based Firewall rule with schedule, NAT/NAPT, SPI Firewall	
VPN Tunnels	100/200	
VPN Function	PPTP server and client, IPSec	
	DES, 3DES and AES encrypting	
	SHA-1/MD5 authentication algorithm	
	VPN Trunk Support	
	Remote access VPN (Client-to-Site) and Site to Site VPN	
Content Filtering	URL, P2P Application, Instant Message and download Blocking Blocks Popup, Java Applet, cookies and Active X	
IDP	Anomaly: Syn Flood, UDP Flood, ICMP Flood and more Pre-defined: Backdoor, DDoS, DoS, Exploit, NetBIOS and Spyware Custom: User defined based on TCP, UDP, ICMP or IP protocol	
Scanned Mail Settings	The allowed size of scanned mail : 10 ~ 512KBytes	
Anti-Virus	Email attachment virus scanning by SMTP, POP3	
	Inbound scanning for internal and external Mail Server	
	Action of infected mail : Delete, Deliver to the recipient, forward to a specific account Automatic or manual update virus database	
Anti-Spam	Inbound scanning for external and internal Mail Server	
	Check sender address in RBL	
	Black list and white list support auto training system	
	Action of spam mail : Delete, Deliver to the recipient, forward to a specific account	
	Up to 100 spam mail rule entries	
QoS	Policy-based bandwidth management	
	Guarantee and maximum bandwidth with 3 priority levels	
	Classify traffics based on IP, IP subnet, TCP/UDP port	
Authentication	Built-in user database with up to 500 entries	
	Support local database, RADIUS and POP3 authentication	
Logs	Log and alarm for event and traffic	
	Log can be saved from web, sent by e-mail or sent to syslog server	
Statistics	Traffic statistic for WAN interface and policies, Graphic display	
Others	Dynamic DNS	
	NTP support	
	DHCP server	
	Virtual server	
	Mapping IP (DMZ)	

APPLICATIONS

Small business, branch offices, and SOHO



ORDERING INFORMATION

CS-1000	Multi-Homing Security Gateway (2 x WAN, 1 x LAN, 1 x DMZ, 200 VPN tunnels)
---------	--